



Data sheet for three-phase Squirrel-Cage-Motors

MLFB-Ordering data : 1LA7096-8AB10

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Electrical data:						
Rated voltage : (1) 230 VD/400 VY, 50 Hz, 460 VY, 60 Hz						
Frequency :			50 Hz			60 Hz
Rated power :			0.55 kW			0.63 kW
Rated speed :			675 1/ min			825 1/ min
Rated torque :			7.8 Nm			7.3 Nm
Rated current (IE) :			VD	VY	VY	
			2.75 A	1.58 A	1.65 A	
Starting / rated current :			3.0			3.0
Breakdown / rated torque :			1.9			1.9
Starting / rated torque :			1.7			1.7
			4/4	3/4	2/4	4/4
Efficiency %			64.0%	63.0%	59.0%	63.9%
Power factor :			0.76	0.70	0.58	0.75
Efficiency class :			-/-			-/-

Mechanical data:		
Sound pressure level 50Hz/60Hz (load) :		
Moment of inertia :		
Bearing DE :		
Bearing NDE :		
Type of bearing :		
Condensate drainage holes :		
Regreasing device :		
Lubricants :		
Grease lifetime/Relubrication interval :		
Quantity of grease for relubrication :		
External earthing terminal :		
Coating :		

Environmental conditions:	
Ambient temperature :	
Altitude above sea level :	
Standards and specifications :	

General data:	
Frame size	
Design of electrical machine :	
Weight in kg, without optional accessories :	
Frame material :	
Degree of protection :	
Method of cooling, TEFC :	
Vibration class :	
Insulation :	
Duty type :	
Direction of rotation :	

Terminal box:	
Material of terminal box :	
Type of terminal box :	
Contact screw thread :	
Max. cross-sectional area :	
Cable diameter from ... to ... :	
Cable entry :	
Cable gland :	

Special design:	
-----------------	--