



Data sheet for three-phase Squirrel-Cage-Motors

MLFB-Ordering data : 1LA7107-8AB10

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Electrical data:

Rated voltage :	(1) 230 VD/400 VY, 50 Hz, 460 VY, 60 Hz					
Frequency :	50 Hz		60 Hz			
Rated power :	1.10 kW		1.30 kW			
Rated speed :	680 1/ min		830 1/ min			
Rated torque :	15.4 Nm		15.0 Nm			
Rated current (IE) :	VD	VY		VY		
	5.04 A	2.90 A		3.00 A		
Starting / rated current :	3.3		3.3			
Breakdown / rated torque :	2.1		2.1			
Starting / rated torque :	1.8		1.8			
	4/4	3/4	2/4	4/4	3/4	2/4
Efficiency %	70.0%	70.0%	66.0%	70.1%	70.1%	66.1%
Power factor :	0.76	0.70	0.58	0.76	0.70	0.58
Efficiency class :	-/-		-/-			

Mechanical data:

Sound pressure level 50Hz/60Hz (load) :	45 dB(A)	48 dB(A)
Moment of inertia :	0.0063 kg*m²	
Bearing DE :	6206 2ZC3	
Bearing NDE :	6205 2ZC3	
Type of bearing :	Floating bearings pre-loaded DE (standard)	
Condensate drainage holes :	No	
Regreasing device :	No	
Lubricants :	Esso Unirex N3	
Grease lifetime/Relubrication interval :	40000 h	
Quantity of grease for relubrication :	null g	
External earthing terminal :	No	
Coating :	Special paint finish RAL 7030 stone gray	

Environmental conditions:

Ambient temperature :	-20 °C - +40 °C
Altitude above sea level :	1000 m
Standards and specifications :	IEC, DIN, ISO, VDE, EN

General data:

Frame size	100 L
Design of electrical machine :	(0) IM B3 / B6 / B7 / B8 / V5 without canopy
Weight in kg, without optional accessories :	22.00 kg
Frame material :	Aluminum
Degree of protection :	IP 55
Method of cooling, TEFC :	IC 411
Vibration class :	A (Standard)
Insulation :	155(F) to 130(B)
Duty type :	S1 - continuous duty
Direction of rotation :	Bi-directional

Terminal box:

Material of terminal box :	
Type of terminal box :	gk 130
Contact screw thread :	
Max. cross-sectional area :	
Cable diameter from ... to ... :	
Cable entry :	
Cable gland :	

Special design: