

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2066A

SIMOTICS GP - 63 M - IM B14 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _i /I _N	T _i /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	0.37	-/-	1.65	2800	1.3	69.5	69.9	66.4	0.81	0.71	0.56	4.4	2.4	2.5	IE2
400	Y	50	0.37	-/-	0.95	2800	1.3	69.5	69.9	66.4	0.81	0.71	0.56	4.4	2.4	2.5	IE2
460	Y	60	0.43	-/-	0.93	3400	1.2	72.0	72.1	69.0	0.81	0.71	0.57	5.2	2.6	2.8	IE2
460	Y	60	0.37	-/-	0.85	3440	1.0	72.0	70.9	66.8	0.76	0.66	0.52	5.9	3.1	3.3	IE2
IM B14 / IM 3601			FS 63 M			IP65	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1.000 m									Locked rotor time (hot / cold) : 13.1 s 18.2 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	55 / 63 dB(A) ^{2) 3)}	59 / 67 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0002 kg m ²		Thermal class	F
Bearing DE NDE	6201 2Z C3	6201 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L_{10mh} $F_{Rad min}$ for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(B) 1 PTC thermistor - for tripping (2 terminals)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 B00	Cable entry	1xM25x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_A/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_K/M_N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1001-0BA62-2KB4-Z						
© Siemens AG 2022	H20			rev.	creation date	language	Page
				929	2022-11-21	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2066A

SIMOTICS GP - 63 M - IM B14 - 2p

Special design

H20 IP 65 degree of protection

Notes:

responsible dep.

DI MC LVM

technical reference

created by

DT Configurator

approved by

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

[Link documents](#)

SIEMENS

document type

datasheet

title

1LE1001-0BA62-2KB4-Z

H20

document status

released

document number

rev.

929

creation date

2022-11-21

language

en

Page

2/2

© Siemens AG 2022

