

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2062B

SIMOTICS GP - 63 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
230	Δ	50	0.12	-/-	0.77	1390	0.8	59.1	56.4	49.0	0.66	0.57	0.45	3.1	2.4	2.5	IE2
400	Y	50	0.12	-/-	0.44	1390	0.8	59.1	56.4	49.0	0.66	0.57	0.45	3.1	2.4	2.5	IE2
460	Y	60	0.14	-/-	0.42	1685	0.8	64.0	61.4	54.8	0.66	0.57	0.46	3.5	2.4	2.7	IE2
460	Y	60	0.12	-/-	0.39	1710	0.7	64.0	60.3	52.2	0.60	0.52	0.41	3.7	2.9	3.2	MG1
IM B5 / IM 3001		FS 63 M		kg		IP55		IEC/EN 60034		IEC, EN, UL, CSA							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 40.4 s | 53.7 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	/ dB(A) ²⁾	/ dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0004 kg m ²		Vibration severity grade	A
Bearing DE NDE	6201 2ZC3	6201 2ZC3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9.0 mm - 17.0 mm
Type of terminal box	TB1 B00	Cable entry	-/-
Contact screw thread	M4	Cable gland	-/-

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_B/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer	
	title 1LE1001-0BB22-2FA4-Z			document number			
© Siemens AG 2021	D31+D40			rev. 01	creation date 2021-04-21 17:30	language en	Page 1/2

SIMOTICS GP - 63 M - IM B5 - 4p

Special design

D31	Version according to UL with "Recognition Mark"	D40	Canadian regulations (CSA)
-----	---	-----	----------------------------

Notes:

responsible dep.		technical reference		created by		approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM				DT Configurator							
		document type				document status			customer		
		datasheet				released					
© Siemens AG 2021		title				document number					
		1LE1001-0BB22-2FA4-Z									
		D31+D40				rev.	creation date		language	Page	
						01	2021-04-21 17:30		en	2/2	