

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2063B

SIMOTICS GP - 63 M - IM B14 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	0.18	-/-	1.07	1385	1.2	64.7	62.4	55.7	0.65	0.56	0.44	3.3	2.6	2.6	IE2
400	Y	50	0.18	-/-	0.62	1385	1.2	64.7	62.4	55.7	0.65	0.56	0.44	3.3	2.6	2.6	IE2
460	Y	60	0.21	-/-	0.60	1685	1.2	68.0	65.8	59.7	0.65	0.56	0.45	3.8	2.8	2.9	IE2
460	Y	60	0.18	-/-	0.56	1710	1.0	68.0	64.4	57.3	0.59	0.50	0.40	3.9	3.3	3.4	IE2
IM B14 / IM 3601			FS 63 M			IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1.000 m									Locked rotor time (hot / cold) : 36.3 s 47.7 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	/ dB(A) ^{2) 3)}	/ dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0004 kg m ²		Thermal class	F
Bearing DE NDE	6201 2Z C3	6201 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L_{10mh} $F_{Rad min}$ for coupling operation	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	mm ²
Material of terminal box		Cable diameter from ... to ...	mm - mm
Type of terminal box		Cable entry	-/-
Contact screw thread		Cable gland	-/-

Notes:

I_A/I_N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_K/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_K/M_N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type				document status		
	datasheet				released		
	title				document number		
	1LE1001-0BB32-2KA4-Z						
© Siemens AG 2022	B07+M10+R71				rev.	creation date	language
					01	2022-07-06	en
						Page	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2063B

SIMOTICS GP - 63 M - IM B14 - 4p

Special design

B07	Supplementary plate, voltage tolerance	R71	ECOFAST motor plug, EMC
M10	Additional rating plate, loose		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				document status released
	title 1LE1001-0BB32-2KA4-Z B07+M10+R71				document number
© Siemens AG 2022				rev. 01	creation date 2022-07-06
				language en	Page 2/2

