

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2066B

SIMOTICS GP - 63 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	0.25	-/-	1.43	1385	1.7	68.5	67.0	61.3	0.64	0.54	0.41	3.7	2.9	2.9	IE2
400	Y	50	0.25	-/-	0.82	1385	1.7	68.5	67.0	61.3	0.64	0.54	0.41	3.7	2.9	2.9	IE2
460	Y	60	0.29	-/-	0.81	1685	1.6	70.0	68.6	63.7	0.64	0.54	0.42	4.2	2.9	3.0	IE2
460	Y	60	0.25	-/-	0.76	1705	1.4	70.0	67.6	61.6	0.59	0.49	0.38	4.5	3.5	3.6	IE2
IM B5 / IM 3001		FS 63 M		IP55		UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 32.3 s 42.7 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	60 / 68 dB(A) ^{2) 3)}	63 / 71 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	kg m ²		Thermal class	F
Bearing DE NDE	6201 2Z C3	6201 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Regreasing device	No		Net weight of the motor (IM B3)	kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	No		Motor protection	(A) without (Standard)
External earthing terminal	No		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 B00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
DI MC LVM		DT Configurator			
	document type				document status
	datasheet				released
	title				document number
	1LE1001-0BB62-2FA4				
© Siemens AG 2022		rev.	creation date	language	Page
		929	2022-12-27	en	1/1