

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2062C

SIMOTICS GP - 63 M - IM B5 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	0.09	-/-	0.84	895	1.0	42.7	38.5	30.4	0.63	0.55	0.46	2.0	1.8	1.9	-/-
400	Y	50	0.09	-/-	0.48	895	1.0	42.7	38.5	30.4	0.63	0.55	0.46	2.0	1.8	1.9	-/-
460	Y	60	0.11	-/-	0.49	1095	1.0	46.6	42.6	35.0	0.60	0.51	0.43	2.2	1.8	2.0	-/-
460	Y	60	0.09	-/-	0.47	1125	0.8	44.9	41.4	32.8	0.53	0.45	0.39	2.3	2.2	2.5	-/-
IM B5 / IM 3001		FS 63 M		IP55				IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 40.3 s 67.8 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	56 / 62 dB(A) ^{2) 3)}	57 / 64 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0003 kg m ²		Thermal class	F
Bearing DE NDE	6201 2Z C3	6201 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	4 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 B00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1001-0BC22-2FA4						
© Siemens AG 2022				rev.	creation date	language	Page
				01	2022-05-31	en	1/1