

SIMOTICS GP - 71 M - IM B14 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ/Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_I/I_N	T_I/T_N	T_B/T_N	
230	Δ	50	0.55	-/-	2.35	2780	1.9	74.1	75.2	72.9	0.80	0.72	0.58	4.6	2.6	2.6	IE2
400	Y	50	0.55	-/-	1.34	2780	1.9	74.1	75.2	72.9	0.80	0.72	0.58	4.6	2.6	2.6	IE2
460	Y	60	0.63	-/-	1.34	3380	1.8	74.0	74.4	71.8	0.80	0.73	0.60	5.1	2.9	2.9	IE2
460	Y	60	0.55	-/-	1.23	3420	1.5	74.0	73.4	69.6	0.76	0.68	0.55	5.4	3.4	3.4	IE2

IM B14 / IM 3601	FS 71 M	kg	IP55	IEC/EN 60034	IEC, DIN, ISO, VDE, EN
------------------	---------	----	------	--------------	------------------------

Locked rotor time (hot / cold) : 22.9 s | 32.7 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	52.0 / 63.0 dB(A) ²⁾	57.0 / 68.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0004 kg m ²		Vibration severity grade	A
Bearing DE NDE	6202 2Z C3	6202 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9.0 mm - 17.0 mm
Type of terminal box	TB1 B00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug


Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>
-------------------------------	---------------------	-------------------------------	-------------	---

	document type	document status		customer	
	datasheet	released			
	title	document number			
	1LE1001-0CA32-2KA4				
© Siemens AG 2021		rev.	creation date	language	Page
		01	2021-04-22 21:51	en	1/1