

SIMOTICS GP - 71 M - IM B14 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_I/I_N	T_I/T_N	T_B/T_N	

DOL duty (S1) - 155(F) to 130(B)

IM B14 / IM 3601		FS 71 M		IP55	UKCA	IEC/EN 60034	IEC, EN, UL		
------------------	--	---------	--	------	------	--------------	-------------	--	--

Locked rotor time (hot / cold) : 22.6 s | 32.3 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	52 / 63 dB(A) ^{2) 3)}	57 / 68 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0004 kg m ²		Thermal class	F
Bearing DE NDE	6202 2Z C3	6202 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	7 kg
Grease nipple	-/-		Coating (paint finish)	No paint finish (cast iron parts primed)
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	1/3 Bi-metallic sensors (opener) for tripping (2 terminals)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 B10	Cable entry	1xM25x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1001-0CA39-0KZ4-Z						
	D31+F01+F10+M1Y+Q3A+S00			rev.	creation date	language	Page
© Siemens AG 2023				943	2023-05-17	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2073A

SIMOTICS GP - 71 M - IM B14 - 2p

Special design

D31	Version according to UL with "Recognition Mark"	M1Y	Non-standard winding:
F01	Mounting of holding brake	Q3A	1/3 Bi-metallic sensors (opener) for tripping (2 terminals)
F10	Brake supply voltage 24 V DC	S00	No paint finish, only GG parts primed

Additional information:

Brake:			
Description:	BFK458-06	Current:	.83 A
Voltage:	DC 24 V	Moment of inertia:	0.000013 kgm²

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	document type datasheet			document status released			
	title 1LE1001-0CA39-0KZ4-Z			document number			
© Siemens AG 2023	D31+F01+F10+M1Y+Q3A+S00			rev. 943	creation date 2023-05-17	language en	Page 2/2