

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2073B

SIMOTICS GP - 71 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
440	Y	60	0.43	-/-	1.09	1680	2.5	72.0	72.4	69.4	0.72	0.63	0.50	4.5	2.6	2.7	IE2
IM B5 / IM 3001		FS 71 M				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 38.4 s | 49.1 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	44 / 55 dB(A) ²⁾	47 / 58 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.0009 kg m ²		Thermal class	F
Bearing DE NDE	6202 2Z C3	6202 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad} min 50 60Hz	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	7 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 B00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type				document status		
	datasheet				released		
	title				document number		
	1LE1001-0CB39-0FA4						
	M1C				rev.	creation date	language Page
© Siemens AG 2022					01	2022-02-21	en 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2073B

SIMOTICS GP - 71 M - IM B5 - 4p

Special design

M1C 440 VY, 60-Hz power

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet			document status released	
	title 1LE1001-0CB39-0FA4 M1C			document number	
© Siemens AG 2022			rev. 01	creation date 2022-02-21	language en
				Page 2/2	