

SIMOTICS GP - 80 M - IM B14 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_l/I_N	T_l/T_N	T_B/T_N	
230	Δ	50	1.50	-/-	5.40	2830	5.1	81.3	83.4	83.6	0.85	0.79	0.67	6.1	2.6	2.8	IE2
400	Y	50	1.50	-/-	3.15	2830	5.1	81.3	83.4	83.6	0.85	0.79	0.67	6.1	2.6	2.8	IE2
460	Y	60	1.75	-/-	3.05	3430	4.8	84.0	85.9	86.1	0.86	0.81	0.71	6.9	2.8	3.0	IE2
460	Y	60	1.50	-/-	2.70	3470	4.2	84.0	85.0	84.0	0.83	0.77	0.66	7.8	3.4	3.6	IE2
IM B14 / IM 3601			FS 80 M		11 kg		IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 10.5 s | 17.2 s

Sound level (SPL / SWL) at 50Hz 60Hz	60.0 / 71.0 dB(A) ²⁾	64.0 / 75.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0013 kg m ²		Vibration severity grade	A
Bearing DE NDE	6004 2Z C3	6004 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box position	top	Max. cross-sectional area	1.5 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9.0 mm - 17.0 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

I_R/I_N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_R/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_B/M_N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title			document number			
	1LE1001-0DA62-2KA4-Z						
	H08			rev.	creation date	language	Page
© Siemens AG 2021				01	2021-04-20 23:41	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2086A

SIMOTICS GP - 80 M - IM B14 - 2p

Special design

H08 Terminal box at the NDE

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1001-ODA62-2KA4-Z							
© Siemens AG 2021	H08	rev. 01	creation date 2021-04-20 23:41		language en	Page 2/2		