

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2082B

SIMOTICS GP - 80 M - IM V1 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

Electrical data

-/-

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N I_f/I_N	M_A/M_N T_f/T_N	M_K/M_N T_B/T_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	0.47	-/-	2.25	1445	3.1	76.9	75.4	70.1	0.69	0.59	0.43	6.1	2.5	3.6	IE2
400	Y	50	0.47	-/-	1.28	1445	3.1	76.9	75.4	70.1	0.69	0.59	0.43	6.1	2.5	3.6	IE2
460	Y	60	0.54	-/-	1.28	1740	3.0	75.7	74.8	70.9	0.70	0.61	0.47	6.5	2.8	3.8	IE2
460	Y	60	0.55	-/-	1.29	1750	3.0	75.5	74.6	71.1	0.71	0.62	0.49	6.4	2.7	3.8	IE2
IM V1 / IM 3011		FS 80 M		IP55		UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +55 °C / 1,000 m

Locked rotor time (hot / cold) : 17.8 s | 23.3 s

These values are calculated. The final rating plate data will be calculated when the order is placed

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	53 / 64 dB(A) ^{2) 3)}	55 / 66 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0017 kg m ²		Thermal class	F
Bearing DE NDE	6004 2Z C3	6004 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
$L_{10mh} F_{Rad, min}$ for coupling operation 50 60Hz ¹⁾	20000 h	16000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	10 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	With		Motor protection	(A) without (Standard)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 gland

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
 2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. IN LVM	technical reference	created by SPC	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
	document type datasheet	document status released			document number
	title 1LE1001-0DB22-2GA4-Z B02+H00+H03+N07+R15	rev. 951	creation date 2023-11-02		
© INNOMOTICS 2023					

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS




Motor type : 1AV2082B

SIMOTICS GP - 80 M - IM V1 - 4p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	N07	Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 55°C, power reduced
H00	Canopy	R15	One metal cable gland
H03	Condensation drain holes in end shield		

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
SIEMENS	document type datasheet	document status released			
	title 1LE1001-0DB22-2GA4-Z B02+H00+H03+N07+R15	document number			
© INNOMOTICS 2023	rev. 951	creation date 2023-11-02	language en	Page 2/2	