

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2082B

SIMOTICS GP - 80 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	$\eta^{3)}$			$\cos\phi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
415	Δ	50	0.50	-/-	1.28	1440	3.3	77.0	76.0	71.4	0.71	0.61	0.46	5.8	2.4	3.4	IE2
480	Δ	60	0.57	-/-	1.27	1740	3.1	75.6	75.1	71.7	0.71	0.63	0.49	6.2	2.6	3.6	IE2
480	Δ	60	0.55	-/-	1.23	1750	3.0	75.5	74.6	71.1	0.71	0.62	0.49	6.4	2.7	3.8	IE2
IM B5 / IM 3001		FS 80 M		10 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +50 °C / 1,000 m

Locked rotor time (hot / cold) : 17.5 s | 23 s

These values are calculated. The final rating plate data will be calculated when the order is placed

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	53.0 / 64.0 dB(A) ²⁾	55.0 / 66.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0017 kg m ²		Vibration severity grade	A
Bearing DE NDE	6004 2Z C3	6004 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(B) 1 PTC thermistor - for tripping (2 terminals)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9.0 mm - 17.0 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1001-0DB23-5FB4-Z			document number				
© Siemens AG 2021	N06			rev. 01	creation date 2021-04-20 20:47	language en	Page 1/2	

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2082B

SIMOTICS GP - 80 M - IM B5 - 4p

Special design

N06 Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 50°C, power reduced

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1001-0DB23-5FB4-Z			document number				
© Siemens AG 2021	N06		rev. 01	creation date 2021-04-20 20:47		language en	Page 2/2	