

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2083B

SIMOTICS GP - 80 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Y	50	0.75	-/-	1.79	1440	5.0	79.6	79.9	77.5	0.76	0.67	0.54	5.6	2.2	3.1	IE2
460	Y	60	0.86	-/-	1.82	1740	4.7	78.0	78.5	76.7	0.76	0.69	0.56	6.2	2.2	3.3	IE2
460	Y	60	0.75	-/-	1.68	1750	4.1	78.0	77.4	74.6	0.72	0.63	0.51	6.8	2.5	3.8	IE2
IM B5 / IM 3001		FS 80 M		11 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 14.8 s | 19.8 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	53.0 / 64.0 dB(A) ²⁾	55.0 / 66.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0021 kg m ²		Vibration severity grade	A
Bearing DE NDE	6004 2Z C3	6004 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9.0 mm - 17.0 mm
Type of terminal box	TB1 E10	Cable entry	1xM25x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_B/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer	
	title 1LE1001-0DB30-2FA4-Z			document number			
© Siemens AG 2021	F01+F12			rev. 01	creation date 2021-04-21 20:21	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2083B

SIMOTICS GP - 80 M - IM B5 - 4p

Special design

F01	Mounting a brake	F12	Brake supply voltage 400 V AC, 50/60 Hz
-----	------------------	-----	---

Additional information:

Brake:

Description:	BFK458-08	Current:	.14 A
Voltage:	AC 400 V	Moment of inertia:	.000045 Nm

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status		customer	
	datasheet	released			
	title	document number			
	1LE1001-0DB30-2FA4-Z				
	F01+F12	rev.	creation date	language	Page
© Siemens AG 2021		01	2021-04-21 20:21	en	2/2