

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2083C

SIMOTICS GP - 80 M - IM B14 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
230	Δ	50	0.55	-/-	2.85	935	5.6	73.1	73.8	70.8	0.66	0.57	0.45	4.4	2.5	2.9	IE2
400	Y	50	0.55	-/-	1.65	935	5.6	73.1	73.8	70.8	0.66	0.57	0.45	4.4	2.5	2.9	IE2
460	Y	60	0.63	-/-	1.76	1135	5.3	68.0	68.4	65.8	0.66	0.58	0.45	4.8	2.6	3.1	IE2
460	Y	60	0.55	-/-	1.66	1145	4.6	68.0	67.4	63.7	0.61	0.52	0.40	5.2	2.9	3.6	MG1

IM B14 / IM 3601	FS 80 M	IP55	IEC/EN 60034	IEC, EN, UL
------------------	---------	------	--------------	-------------

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 21.4 s | 29.8 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	42 / 53 dB(A) ²⁾	45 / 56 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.0025 kg m ²		Insulation	155(F) to 130(B)
Bearing DE NDE	6004 2Z C3	6004 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} , F _{Rad min} 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	12 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number		
	1LE1001-0DC32-2KA4-Z D31			
© Siemens AG 2021	rev.	creation date	language	Page
	01	2021-09-23 08:48	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2083C

SIMOTICS GP - 80 M - IM B14 - 6p

Special design

D31	Version according to UL with "Recognition Mark"
-----	---

Additional information:

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title			document number			
	1LE1001-0DC32-2KA4-Z						
© Siemens AG 2021	D31			rev.	creation date	language	Page
				01	2021-09-23 08:48	en	2/2