

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2090A

SIMOTICS GP - 90 S - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\phi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
230	Δ	50	1.50	-/-	5.50	2900	5.0	81.3	81.7	79.7	0.84	0.77	0.63	6.9	2.7	3.6	IE2
400	Y	50	1.50	-/-	3.15	2900	5.0	81.3	81.7	79.7	0.84	0.77	0.63	6.9	2.7	3.6	IE2
460	Y	60	1.75	-/-	3.10	3480	4.8	84.0	84.4	82.6	0.85	0.79	0.68	7.4	2.6	3.8	IE2
460	Y	60	1.50	-/-	2.75	3505	4.1	84.0	83.5	80.7	0.82	0.74	0.62	8.5	3.1	4.5	IE2
IM B3 / IM 1001		FS 90 S		13 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 6.55 s | 10.9 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	65.0 / 77.0 dB(A) ²⁾	69.0 / 81.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0017 kg m ²		Vibration severity grade	A
Bearing DE NDE	6205 2Z C3	6004 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L_{10mh} $F_{rad min}$ for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Special paint finish C3
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(B) 1 PTC thermistor - for tripping (2 terminals)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9.0 mm - 17.0 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_K/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released		customer			
	title 1LE1001-0EA02-2AB4-Z D22+D47+S02+Y53	document number					
© Siemens AG 2021		rev. 01	creation date 2021-04-23 15:38	language en	Page 1/2		

SIMOTICS GP - 90 S - IM B3 - 2p

D22	motor without CE character for export outside the EEA (see EU regulation 640/2009)	S02	Special paint finish C3
D47	TR CU product safety certificate EAC for the Eurasian Customs Union	Y53	Paint finish in other standard RAL colours

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer	
	title 1LE1001-0EA02-2AB4-Z			document number			
© Siemens AG 2021	D22+D47+S02+Y53			rev. 01	creation date 2021-04-23 15:38	language en	Page 2/2