

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2090D

SIMOTICS GP - 90 S - IM B5 - 8p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL	
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N		
230	Δ	50	0.37	-/-	2.35	675	5.2	56.1	55.6	49.6	0.71	0.60	0.47	2.6	1.4	1.7	IE2	
400	Y	50	0.37	-/-	1.34	675	5.2	56.1	55.6	49.6	0.71	0.60	0.47	2.6	1.4	1.7	IE2	
460	Y	60	0.43	-/-	1.33	830	5.0	58.0	57.5	52.5	0.70	0.59	0.46	2.9	1.4	1.8	IE2	
460	Y	60	0.37	-/-	1.25	845	4.2	58.0	55.8	49.5	0.64	0.54	0.42	3.0	1.6	2.1	IE2	
IM B5 / IM 3001		FS 90 S				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 43.2 s 67.4 s									

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	53 / 65 dB(A) ²⁾	57 / 69 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.0019 kg m ²		Insulation	155(F) to 130(B)
Bearing DE NDE	6205 2Z C3	6004 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} , F _{Rad min} 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	11 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type	document status		customer			
	datasheet	released					
	title	document number					
	1LE1001-0ED02-2FA4						
© Siemens AG 2021		rev.	creation date	language	Page		
		01	2021-10-04 12:14	en	1/1		