

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2104B

SIMOTICS GP - 100 L - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
220	Δ	50	2.20	-/-	8.50	1455	14.4	84.3	85.1	84.2	0.81	0.74	0.62	6.9	2.1	3.3	IE2
380	Y	50	2.20	-/-	4.90	1455	14.4	84.3	85.1	84.2	0.81	0.74	0.62	6.9	2.1	3.3	IE2
440	Y	60	2.54	-/-	4.65	1755	13.9	87.5	87.9	87.3	0.82	0.79	0.65	7.3	2.1	3.3	IE2
440	Y	60	2.20	-/-	4.25	1760	11.9	87.5	88.3	87.4	0.78	0.74	0.63	8.1	2.5	3.9	IE2

IM B5 / IM 3001		FS 100 L	21 kg	IP65		IEC/EN 60034	IEC, DIN, ISO, VDE, EN		
-----------------	--	----------	-------	------	--	--------------	------------------------	--	--

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 11.5 s | 16.4 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	60.0 / 72.0 dB(A) ²⁾	62.0 / 74.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0086 kg m ²		Vibration severity grade	A
Bearing DE NDE	6206 2Z C3	6206 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	4.0 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 F00	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_B/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
© Siemens AG 2021	title	document number	language	
	1LE1001-1AB42-1FA4-Z H20+P02	rev.		
		creation date	2021-04-23 14:03	Page
			01	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2104B

SIMOTICS GP - 100 L - IM B5 - 4p

Special design

H20 IP 65 degree of protection P02 Next smaller flange

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet				document status released		customer	
	title 1LE1001-1AB42-1FA4-Z				document number			
© Siemens AG 2021	H20+P02				rev. 01	creation date 2021-04-23 14:03	language en	Page 2/2