

SIMOTICS GP - 100 L - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

--

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
230	Δ	50	3.00	-/-	10.70	1455	19.7	85.5	86.4	85.6	0.82	0.76	0.64	6.9	2.0	3.1	IE2
400	Y	50	3.00	-/-	6.20	1455	19.7	85.5	86.4	85.6	0.82	0.76	0.64	6.9	2.0	3.1	IE2
460	Y	60	3.45	-/-	6.00	1755	18.8	87.5	88.2	87.3	0.82	0.77	0.65	7.5	2.0	3.1	IE2
460	Y	60	3.00	-/-	5.40	1765	16.2	87.5	87.5	86.0	0.79	0.72	0.60	8.3	2.4	3.7	IE2
IM B5 / IM 3001			FS 100 L		25 kg		IP55	IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Locked rotor time (hot / cold) : 9.57 s | 14.6 s

Sound level (SPL / SWL) at 50Hz 60Hz	60.0 / 72.0 dB(A) ²⁾	62.0 / 74.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0140 kg m ²		Vibration severity grade	A
Bearing DE NDE	6206 2Z C3	6206 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad,min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box position	top	Max. cross-sectional area	4.0 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 F00	Cable entry	2xM32x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	3 plugs

I_r/I_n = locked rotor current / current nominal M_r/M_n = locked rotor torque / torque nominal M_b/M_n = break down torque / nominal torque	1) L10mh according to DIN ISO 281 10/2010 2) at rated power / at full load	3) Value is valid only for DOL operation with motor design IC411
--	---	--

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title		document number				
	1LE1001-1AB52-2FA4-Z						
	F01+F10		rev.	creation date	language	Page	
© Siemens AG 2021			01	2021-04-21 13:38	en	1/2	

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2105B

SIMOTICS GP - 100 L - IM B5 - 4p

Special design

F01 Mounting a brake F10 Brake supply voltage 24 V DC

Additional information:

Brake:

Description: BFK458-12 Current: 1.67 A
Voltage: DC 24 V Moment of inertia: .00036 Nm

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
-------------------------------	---------------------	-------------------------------	-------------	--

	document type datasheet	document status released		customer	
	title 1LE1001-1AB52-2FA4-Z F01+F10	document number			
© Siemens AG 2021		rev. 01	creation date 2021-04-21 13:38	language en	Page 2/2