

Data sheet for three-phase Squirrel-Cage-Motors INNOMOTICS



Motor type : 1AV2106B INNOMOTICS GP - 100 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

Electrical data -/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 155(F)																	
230	Δ	50	4.00	-/-	14.50	1460	26.0	86.6	88.0	87.5	0.80	0.74	0.62	7.5	2.2	3.5	IE2
400	Y	50	4.00	-/-	8.30	1460	26.0	86.6	88.0	87.5	0.80	0.74	0.62	7.5	2.2	3.5	IE2
460	Y	60	4.55	-/-	8.10	1760	24.5	87.5	88.6	88.1	0.81	0.76	0.65	7.9	2.2	3.4	IE2
460	Y	60	3.70	-/-	7.00	1770	20.0	87.5	87.7	86.3	0.76	0.69	0.57	9.2	2.8	4.3	MG1
IM B3 / IM 1001		FS 100 L				IP55	UKCA	IEC/EN 60034		IEC, EN, UL							
Environmental conditions : -30 °C - +55 °C / 1000 m									Locked rotor time (hot / cold) : 8.1 s 12.6 s								

Mechanical data				
Sound level (SPL / SWL) at 50Hz 60Hz	60 / 72 dB(A) ^{2) 3)}	62 / 74 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0140 kg m ²		Thermal class	F
Bearing DE NDE	6206 2Z C3	6206 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	30 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(A) without (Standard)
External earthing terminal	Without		Method of cooling	IC418 - without fan and without housing fan

Terminal box																	
Terminal box position			top			Max. cross-sectional area			4 mm ²								
Material of terminal box			Aluminium			Cable diameter from ... to ...			11 mm - 21 mm								
Type of terminal box			TB1 F00			Cable entry			2xM32x1,5								
Contact screw thread			M4			Cable gland			2 plugs								

I_A/I_N = locked rotor current / current nominal 1) L_{10mh} according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411

M_A/M_N = locked rotor torque / torque nominal 2) at rated power / at full load

M_K/M_N = break down torque / nominal torque

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents 	
INNOMOTICS	Document type Technical data sheet			Document status Released			
	Document title 1LE1001-1AB62-2AA4-Z			Document number TDS-240923-125458			
	Restricted © Innomotics 2024			Revision AA	Creation date 2024-09-23		

INNOMOTICS GP - 100 L - IM B3 - 4p

D04	Minimum ambient temperature -30°C	H07	Stainless steel screws and bolts (outside the motor)
D22	Motor without CE character for export outside the EEA (see EU regulation 2019/1781)	H08	Terminal box at the NDE
D31	Version according to UL with "Recognition Mark"	N03	Temperature class 155 (F), utilised to 155 (F), with increased cooling medium temperature
F90	Without external fan and without external fan cover		

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference SPC	Created by Created automatically	Approved by Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents 	
	Document type Technical data sheet		Document status Released			
	Document title 1LE1001-1AB62-2AA4-Z		Document number TDS-240923-125458			
Restricted © Innomotics 2024	D04+D22+D31+F90+H07+H08+N03		Revision AA	Creation date 2024-09-23	Language en	Page 2/2