

SIMOTICS GP - 100 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
230	Δ	50	4.00	-/-	14.50	1460	26.0	86.6	88.0	87.5	0.80	0.74	0.62	7.5	2.2	3.5	IE2
400	Y	50	4.00	-/-	8.30	1460	26.0	86.6	88.0	87.5	0.80	0.74	0.62	7.5	2.2	3.5	IE2
460	Y	60	4.55	-/-	8.10	1760	24.5	87.5	88.6	88.1	0.81	0.76	0.65	7.9	2.2	3.4	IE2
460	Y	60	3.70	-/-	7.00	1770	20.0	87.5	87.7	86.3	0.76	0.69	0.57	9.2	2.8	4.3	IE2
IM B3 / IM 1001			FS 100 L		30 kg		IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					

Environmental conditions : -30 °C - + °C / 1,000 m

Locked rotor time (hot / cold) : 7.85 s | 12.2 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	60.0 / 72.0 dB(A) ²⁾	62.0 / 74.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0140 kg m ²		Vibration severity grade	A
Bearing DE NDE	6206 2Z C3	6206 2Z C3	Insulation	155(F) to 155(F)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC418 - without fan and without housing fan

Terminal box

Terminal box position	top	Max. cross-sectional area	4.0 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 F00	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer	
	title 1LE1001-1AB62-2AA4-Z			document number			
© Siemens AG 2021	D04+F90+H08+N03			rev. 01	creation date 2021-04-22 17:49	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2106B

SIMOTICS GP - 100 L - IM B3 - 4p

Special design

D04	Minimum ambient temperature -30°C	H08	Terminal box at the NDE
F90	Without external fan and without external fan cover	N03	Temperature class 155 (F), utilised to 155 (F), with increased cooling medium temperature

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1001-1AB62-2AA4-Z							
© Siemens AG 2021	D04+F90+H08+N03	rev. 01	creation date 2021-04-22 17:49		language en	Page 2/2		