

SIMOTICS GP - 132 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
230	Δ	50	7.50	-/-	25.50	1465	49.0	88.7	89.8	89.8	0.83	0.78	0.69	6.9	2.3	2.9	IE2
400	Y	50	7.50	-/-	14.70	1465	49.0	88.7	89.8	89.8	0.83	0.78	0.69	6.9	2.3	2.9	IE2
460	Y	60	8.60	-/-	14.50	1765	46.5	89.5	90.0	90.1	0.83	0.81	0.71	7.1	2.3	2.9	IE2
460	Y	60	7.50	-/-	12.80	1770	40.5	89.5	90.0	89.3	0.82	0.78	0.68	8.0	2.7	3.4	IE2
IM B5 / IM 3001			FS 132 M		49 kq		IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					

Locked rotor time (hot / cold) : 12.2 s | 21.3 s

Sound level (SPL / SWL) at 50Hz 60Hz	64.0 / 76.0 dB(A) ²⁾	68.0 / 80.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0280 kg m ²		Vibration severity grade	A
Bearing DE NDE	6208 2Z C3	6208 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box position	top	Max. cross-sectional area	6.0 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 H00	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

I_{n}/I_{N} = locked rotor current / current nominal	1) L10mhh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_{n}/M_{N} = locked rotor torque / torque nominal	2) at rated power / at full load	
M_{b}/M_{N} = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title			document number			
	1LE1001-1CB22-2FA4						
© Siemens AG 2021				rev.	creation date	language	Page
				01	2021-04-21 22:46	en	1/1