

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2132B

SIMOTICS GP - 132 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	7.50	-/-	14.70	1465	49.0	88.7	89.8	89.8	0.83	0.78	0.69	6.9	2.3	2.9	IE2
690	Y	50	7.50	-/-	8.50	1465	49.0	88.7	89.8	89.8	0.83	0.78	0.69	6.9	2.3	2.9	IE2
460	Δ	60	8.60	-/-	14.50	1765	46.5	89.5	90.0	90.1	0.83	0.81	0.71	7.1	2.3	2.9	IE2
460	Δ	60	7.50	-/-	12.80	1770	40.5	89.5	90.0	89.3	0.82	0.78	0.68	8.0	2.7	3.4	IE2
IM B5 / IM 3001		FS 132 M		49 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 12.2 s | 21.3 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	64.0 / 76.0 dB(A) ²⁾	68.0 / 80.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0280 kg m ²		Vibration severity grade	A
Bearing DE NDE	6208 2Z C3	6208 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	6.0 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 H00	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_B/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator						
	document type			document status		customer		
	datasheet			released				
	title			document number				
	1LE1001-1CB23-4FA4							
© Siemens AG 2021				rev.	creation date	language	Page	
				01	2021-04-20 13:11	en	1/1	