

SIMOTICS GP - 132 S - IM B35 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_I/I_N	T_I/T_N	T_B/T_N	
380	Δ	50	3.00	-/-	7.60	970	29.5	83.3	83.4	81.0	0.72	0.63	0.50	5.0	1.6	2.5	IE2
660	Y	50	3.00	-/-	4.40	970	29.5	83.3	83.4	81.0	0.72	0.63	0.50	5.0	1.6	2.5	IE2
440	Δ	60	3.45	-/-	7.20	1170	28.0	87.5	87.9	86.2	0.72	0.64	0.51	5.2	1.6	2.6	IE2
440	Δ	60	3.00	-/-	6.50	1175	24.5	87.5	87.2	84.7	0.69	0.60	0.47	6.0	1.8	2.9	IE2

IM B35 / IM 2001	FS 132 S	38 kg	IP55	IEC/EN 60034	IEC, DIN, ISO, VDE, EN
------------------	----------	-------	------	--------------	------------------------

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 27.1 s | 41.5 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	63.0 / 75.0 dB(A) ²⁾	67.0 / 79.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0240 kg m ²		Vibration severity grade	A
Bearing DE NDE	6208 2Z C3	6208 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	6.0 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 H00	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs


Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>
-------------------------------	---------------------	-------------------------------	-------------	---

	document type	document status		customer	
	datasheet	released			
	title	document number			
	1LE1001-1CC03-3JA4				
© Siemens AG 2021		rev.	creation date	language	Page
		01	2021-04-22 00:10	en	1/1