

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2162B

SIMOTICS GP - 160 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
400	Δ	50	11.00	-/-	21.00	1470	71.0	89.8	91.0	90.9	0.85	0.82	0.73	6.7	2.1	2.8	IE2
690	Y	50	11.00	-/-	12.10	1470	71.0	89.8	91.0	90.9	0.85	0.82	0.73	6.7	2.1	2.8	IE2
460	Δ	60	12.60	-/-	20.50	1770	68.0	91.0	91.7	91.1	0.85	0.83	0.75	7.0	2.2	2.8	IE2
460	Δ	60	11.00	-/-	18.10	1775	59.0	91.0	91.2	90.1	0.84	0.80	0.71	7.7	2.5	3.2	IE2

IM B3 / IM 1001		FS 160 M	71 kg	IP55		IEC/EN 60034	IEC, DIN, ISO, VDE, EN										
-----------------	--	----------	-------	------	--	--------------	------------------------	--	--	--	--	--	--	--	--	--	--

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 17.9 s | 28.8 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	65.0 / 77.0 dB(A) ²⁾	69.0 / 81.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0550 kg m ²		Vibration severity grade	A
Bearing DE NDE	6309 2Z C3	6209 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	left	Max. cross-sectional area	16.0 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J00	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_K/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number	rev.	creation date
	1LE1001-1DB23-4AB6-Z		01	2021-04-21 19:42
	L22			
© Siemens AG 2021			language	Page
			en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2162B

SIMOTICS GP - 160 M - IM B3 - 4p

Special design

L22 Bearing design for increased cantilever forces

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1001-1DB23-4AB6-Z							document number
© Siemens AG 2021	L22	rev. 01	creation date 2021-04-21 19:42		language en	Page 2/2		