

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2184B

SIMOTICS GP - 180 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
240	Δ	50	22.00	-/-	69.00	1465	143.0	91.6	92.2	91.9	0.84	0.79	0.69	7.3	2.6	3.5	IE2
415	Y	50	22.00	-/-	40.00	1465	143.0	91.6	92.2	91.9	0.84	0.79	0.69	7.3	2.6	3.5	IE2
480	Y	60	25.30	-/-	38.50	1765	137.0	92.4	92.9	92.5	0.85	0.80	0.72	7.5	2.6	3.4	IE2
480	Y	60	22.00	-/-	34.50	1770	119.0	92.4	92.5	91.8	0.83	0.78	0.68	8.4	3.0	3.9	IE2
IM B3 / IM 1001		FS 180 L		132 kg		IP55	IEC/EN 60034		IEC, DIN, ISO, VDE, EN								
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 9.79 s 18.7 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	69.0 / 76.0 dB(A) ²⁾	72.0 / 79.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.1300 kg m ²		Vibration severity grade	A
Bearing DE NDE	6210 Z C3	6210 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16.0 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J00	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal

M_K/M_N = locked rotor torque / torque nominal

M_B/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010

2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type	datasheet		document status		customer	
				released			
	title	1LE1001-1EB42-3AA4		document number			
© Siemens AG 2021			rev.	creation date		language	Page
			01	2021-04-22 20:20		en	1/1