



**SIMOTICS GP - 180 L - IM B3 - 6p**

|                  |                 |           |
|------------------|-----------------|-----------|
| Client order no. | Item-No.        | Offer no. |
| Order no.        | Consignment no. | Project   |

|         |
|---------|
| Remarks |
|---------|

## Safe Area

| U   | $\Delta / Y$ | f    | P    | P    | I   | n       | M    | $\eta^{3)}$ |     |     | $\cos\varphi^{3)}$ |     |     | $I_A/I_N$ | $M_A/M_N$ | $M_K/M_N$ | IE-CL |
|-----|--------------|------|------|------|-----|---------|------|-------------|-----|-----|--------------------|-----|-----|-----------|-----------|-----------|-------|
| [V] |              | [Hz] | [kW] | [hp] | [A] | [1/min] | [Nm] | 4/4         | 3/4 | 2/4 | 4/4                | 3/4 | 2/4 | $I_A/I_N$ | $T_I/T_N$ | $T_B/T_N$ |       |

**DOL duty (S1) - 155(F) to 130(B)**

|                 |          |      |      |              |                        |
|-----------------|----------|------|------|--------------|------------------------|
| IM B3 / IM 1001 | FS 180 L | IP55 | UKCA | IEC/EN 60034 | IEC, DIN, ISO, VDE, EN |
|-----------------|----------|------|------|--------------|------------------------|

Locked rotor time (hot / cold) : 24.7 s | 41.2 s

## Mechanical data

|                                                                                     |                                |                                |                                 |                                                    |
|-------------------------------------------------------------------------------------|--------------------------------|--------------------------------|---------------------------------|----------------------------------------------------|
| Sound level (SPL / SWL) at 50Hz 60Hz                                                | 57 / 70 dB(A) <sup>2) 3)</sup> | 60 / 73 dB(A) <sup>2) 3)</sup> | Vibration severity grade        | A                                                  |
| Moment of inertia                                                                   | 0.1700 kg m²                   |                                | Thermal class                   | F                                                  |
| Bearing DE   NDE                                                                    | 6210 2Z C3                     | 6210 2Z C3                     | Duty type                       | S1                                                 |
| <b>bearing lifetime</b>                                                             |                                |                                | Direction of rotation           | bidirectional                                      |
| $\frac{L_{10mh}}{50 60Hz} \cdot F_{Rad \ min}$ for coupling operation <sup>1)</sup> | 40000 h                        | 32000 h                        | Frame material                  | aluminum                                           |
| Regreasing device                                                                   | No                             |                                | Net weight of the motor (IM B3) | 121 kg                                             |
| Grease nipple                                                                       | -/-                            |                                | Coating (paint finish)          | Standard paint finish C2                           |
| Type of bearing                                                                     | Locating bearing NDE           |                                | Color, paint shade              | RAL7030                                            |
| Condensate drainage holes                                                           | No                             |                                | Motor protection                | (B) 3 PTC thermistors - for tripping (2 terminals) |
| External earthing terminal                                                          | No                             |                                | Method of cooling               | IC411 - self ventilated, surface cooled            |

## Terminal box

|                          |           |                                |                     |
|--------------------------|-----------|--------------------------------|---------------------|
| Terminal box position    | top       | Max. cross-sectional area      | 16 mm²              |
| Material of terminal box | Aluminium | Cable diameter from ... to ... | 19 mm - 28 mm       |
| Type of terminal box     | TB1 J00   | Cable entry                    | 2xM40x1,5-1xM16x1,5 |
| Contact screw thread     | M5        | Cable gland                    | 3 plugs             |

Notes:

$I_A/I_N$  = locked rotor current / current nominal  
 $M_A/M_N$  = locked rotor torque / torque nominal  
 $M_K/M_N$  = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010  
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

|                                                                                    |                      |                 |             |                                                                                                              |               |                                                                                       |      |
|------------------------------------------------------------------------------------|----------------------|-----------------|-------------|--------------------------------------------------------------------------------------------------------------|---------------|---------------------------------------------------------------------------------------|------|
| responsible dep.                                                                   | technical reference  | created by      | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |               | <a href="#">Link documents</a>                                                        |      |
| DI MC LVM                                                                          |                      | DT Configurator |             |                                                                                                              |               |  |      |
|  | document type        |                 |             | document status                                                                                              |               |  |      |
|                                                                                    | datasheet            |                 |             | released                                                                                                     |               |                                                                                       |      |
|                                                                                    | title                |                 |             | document number                                                                                              |               |                                                                                       |      |
|                                                                                    | 1LE1001-1EC49-0AB4-Z |                 |             |                                                                                                              |               |                                                                                       |      |
|                                                                                    | B02+D22+M1Y          |                 |             | rev.                                                                                                         | creation date | language                                                                              | Page |
| © Siemens AG 2023                                                                  |                      |                 |             | 942                                                                                                          | 2023-02-08    | en                                                                                    | 1/2  |



**SIMOTICS GP - 180 L - IM B3 - 6p**

|     |                                                                                     |     |                       |
|-----|-------------------------------------------------------------------------------------|-----|-----------------------|
| B02 | Acceptance test certificate 3.1 acc. to EN 10204                                    | M1Y | Non-standard winding: |
| D22 | Motor without CE character for export outside the EEA (see EU regulation 2019/1781) |     |                       |

|        |
|--------|
| Notes: |
|        |

|                                                                                    |                               |                               |             |                                                                                                              |                             |                                                                                       |             |
|------------------------------------------------------------------------------------|-------------------------------|-------------------------------|-------------|--------------------------------------------------------------------------------------------------------------|-----------------------------|---------------------------------------------------------------------------------------|-------------|
| responsible dep.<br>DI MC LVM                                                      | technical reference           | created by<br>DT Configurator | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                             | <a href="#">Link documents</a>                                                        |             |
|  | document type<br>datasheet    |                               |             | document status<br>released                                                                                  |                             |  |             |
|                                                                                    | title<br>1LE1001-1EC49-0AB4-Z |                               |             | document number                                                                                              |                             |                                                                                       |             |
| © Siemens AG 2023                                                                  | B02+D22+M1Y                   |                               |             | rev.<br>942                                                                                                  | creation date<br>2023-02-08 | language<br>en                                                                        | Page<br>2/2 |