

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1072B

SIMOTICS GP - 71 M - IM B35 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _i /I _N	T _i /T _N	T _B /T _N	
230	Δ	50	0.25	-/-	1.40	1365	1.8	61.5	61.4	56.1	0.73	0.63	0.49	3.0	1.8	2.0	IE1
400	Y	50	0.25	-/-	0.80	1365	1.8	61.5	61.4	56.1	0.73	0.63	0.49	3.0	1.8	2.0	IE1
460	Y	60	0.28	-/-	0.75	1665	1.7	68.0	67.8	62.6	0.71	0.61	0.48	3.4	1.8	2.0	IE1
IM B35 / IM 2001			FS 71 M				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1.000 m									Locked rotor time (hot / cold) : 26.4 s 44 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	49 / 60 dB(A) ²⁾	51 / 62 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.0005 kg m ²		Insulation	155(F) to 130(B)
Bearing DE NDE	6202 2Z C3	6202 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} , F _{Rad min} 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 B00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I_A/I_N = locked rotor current / current nominal
 M_K/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque
¹⁾ L10mh according to DIN ISO 281 10/2010
²⁾ at rated power / at full load
³⁾ Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer	
	title 1LE1002-0CB22-2JA4			document number			
© Siemens AG 2021			rev. 01	creation date 2021-10-08 09:14	language en	Page 1/1	