

GP motor type: 1AV1073B low-voltage motor, IEC squirrel-cage rotor, self-cooled, IP 55 temperature class 155(F) according to 130(B) aluminum enclosure Standard Efficiency IE1, in EEA: minimum efficiency according to (EU) 2019/1781 is IE2 (as of 01.07.2021) 4-pole * size 71M * 0.37 kW (50 Hz) 0.43 kW(60 Hz) standard color RAL 7030 if no order code is specified for selecting another color. The product will be delivered with either the Siemens or Innomotics product brand. 3 AC 50 Hz 230 VD/400 VY * 3 AC 60 Hz 460 VY IM B 5, flange: FF130 (A160) Without motor protection terminal box at top D03=Coolant temperature -40 to +40 °C D22=Motor without CE mark for export outside of EEA (see EU Directive 2019/1781) D47=TR CU product safety certificate EAC for Eurasian customs union F01=built-on holding brake F12=Brake control voltage 400 V AC, 50/60 Hz F50=Mechanical-manual release of brake with actuating lever

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com>

