

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1073C

SIMOTICS GP - 71 M - IM B14 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
230	Δ	50	0.25	-/-	1.70	860	2.8	52.1	52.8	48.4	0.71	0.59	0.46	2.2	2.0	2.0	IE1
400	Y	50	0.25	-/-	0.98	860	2.8	52.1	52.8	48.4	0.71	0.59	0.46	2.2	2.0	2.0	IE1
460	Y	60	0.28	-/-	0.90	1070	2.6	57.5	58.1	54.2	0.70	0.59	0.46	2.5	2.0	2.1	IE1
IM B14 / IM 3601		FS 71 M		kg		IP55		IEC/EN 60034		IEC, EN, NEMA MG1-12							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 60.6 s | 86.1 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	51.0 / 62.0 dB(A) ²⁾	53.0 / 64.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0008 kg m ²		Vibration severity grade	A
Bearing DE NDE	6202 2Z C3	6202 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9.0 mm - 17.0 mm
Type of terminal box	TB1 B00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_B/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type	datasheet		document status	released		
	title	1LE1002-0CC32-2KA4-Z		document number			
© Siemens AG 2021	D30			rev.	creation date	language	Page
				01	2021-04-22 12:35	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1073C

SIMOTICS GP - 71 M - IM B14 - 6p

Special design

D30 Electrical design according to NEMA MG1-12

Notes:

responsible dep. DI MC LVM		technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.				
		document type datasheet			document status released		customer		
		title 1LE1002-0CC32-2KA4-Z			document number				
© Siemens AG 2021		D30				rev. 01	creation date 2021-04-22 12:35	language en	Page 2/2