

SIMOTICS GP - 80 M - IM B14 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
230	Δ	50	0.55	-/-	2.50	1385	3.8	70.0	70.7	67.7	0.79	0.69	0.55	3.7	2.1	2.2	IE1
400	Y	50	0.55	-/-	1.44	1385	3.8	70.0	70.7	67.7	0.79	0.69	0.55	3.7	2.1	2.2	IE1
460	Y	60	0.63	-/-	1.37	1685	3.5	74.0	74.2	71.4	0.78	0.69	0.56	4.3	2.3	2.5	IE1
IM B14 / IM 3601			FS 80 M		kg		IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 22.5 s | 36.5 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	53.0 / 64.0 dB(A) ²⁾	55.0 / 66.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0028 kg m ²		Vibration severity grade	A
Bearing DE NDE	6004 2Z C3	6004 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9.0 mm - 17.0 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator						
	document type	datasheet			document status		customer	
					released			
	title	1LE1002-0DB22-2KA4-Z			document number			
	F01+F11+G11							
© Siemens AG 2021			rev.	creation date	language	Page		
			01	2021-04-22 19:04	en	1/2		

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1082B

SIMOTICS GP - 80 M - IM B14 - 4p

Special design

F01	Mounting a brake	G11	Rotary pulse encoder Sendix 5020 (HTL)
F11	Brake supply voltage, 230 V AC, 50/60 Hz		

Additional information:

Brake:

Description:	BFK458-08	Current:	.12 A
Voltage:	AC 230 V	Moment of inertia:	.000045 Nm

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet				document status released		customer	
	title 1LE1002-0DB22-2KA4-Z F01+F11+G11				document number			
© Siemens AG 2021				rev. 01	creation date 2021-04-22 19:04	language en	Page 2/2	