

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1082B

SIMOTICS GP - 80 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
460	Δ	60	0.63	-/-	1.37	1685	3.5	74.0	74.2	71.4	0.78	0.69	0.56	4.3	2.3	2.5	IE1
IM B5 / IM 3001			FS 80 M		kg		IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1,000 m										Locked rotor time (hot / cold) : 22.5 s 36.5 s							

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	53.0 / 64.0 dB(A) ²⁾	55.0 / 66.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0028 kg m ²		Vibration severity grade	A
Bearing DE NDE	6004 2Z C3	6004 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	left	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9.0 mm - 17.0 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
SIEMENS	document type datasheet			document status released		customer	
	title 1LE1002-0DB29-0FA6-Z			document number			
	© Siemens AG 2021	B02+F01+F11+F76+M1F			rev. 01	creation date 2021-04-22 12:13	language en

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1082B

SIMOTICS GP - 80 M - IM B5 - 4p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	F76	Metal external fan
F01	Mounting a brake	M1F	460 VD for 60 Hz, 60-Hz power
F11	Brake supply voltage, 230 V AC, 50/60 Hz		

Additional information:

Brake:

Description:	BFK458-08	Current:	.12 A
Voltage:	AC 230 V	Moment of inertia:	.000045 Nm

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1002-0DB29-0FA6-Z B02+F01+F11+F76+M1F							document number
© Siemens AG 2021		rev. 01	creation date 2021-04-22 12:13		language en	Page 2/2		