

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1094B

SIMOTICS GP - 90 L - IM B35 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	1.50	-/-	3.50	1410	10.2	77.2	77.8	75.1	0.80	0.71	0.57	4.7	2.4	2.6	IE1
690	Y	50	1.50	-/-	2.05	1410	10.2	77.2	77.8	75.1	0.80	0.71	0.57	4.7	2.4	2.6	IE1
460	Δ	60	1.75	-/-	3.45	1710	9.8	78.7	79.2	76.7	0.81	0.73	0.59	5.4	2.6	2.8	-/-
IM B35 / IM 2001		FS 90 L		kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 9.56 s 18.8 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	58.0 / 69.0 dB(A) ²⁾	55.0 / 66.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0060 kg m ²		Vibration severity grade	A
Bearing DE NDE	6205 2Z C3	6004 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9.0 mm - 17.0 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title			document number			
	1LE1002-0EB43-4JA4-Z						
© Siemens AG 2021	D22+D47			rev.	creation date	language	Page
				01	2021-04-21 23:19	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1094B

SIMOTICS GP - 90 L - IM B35 - 4p

Special design

D22	motor without CE character for export outside the EEA (see EU regulation 640/2009)	D47	TR CU product safety certificate EAC for the Eurasian Customs Union
-----	--	-----	---

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1002-0EB43-4JA4-Z							
© Siemens AG 2021	D22+D47	rev. 01	creation date 2021-04-21 23:19		language en	Page 2/2		