

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1104B

SIMOTICS GP - 100 L - IM B5 - 4p

|                  |                 |           |
|------------------|-----------------|-----------|
| Client order no. | Item-No.        | Offer no. |
| Order no.        | Consignment no. | Project   |

Remarks

Electrical data

Safe Area

| U                                                    | Δ / Y | f        | P    | P     | I    | n       | M    | η <sup>3)</sup> |                                                  |                        | cosφ <sup>3)</sup> |      |      | I <sub>A</sub> /I <sub>N</sub> | M <sub>A</sub> /M <sub>N</sub> | M <sub>K</sub> /M <sub>N</sub> | IE-CL |
|------------------------------------------------------|-------|----------|------|-------|------|---------|------|-----------------|--------------------------------------------------|------------------------|--------------------|------|------|--------------------------------|--------------------------------|--------------------------------|-------|
| [V]                                                  |       | [Hz]     | [kW] | [hp]  | [A]  | [1/min] | [Nm] | 4/4             | 3/4                                              | 2/4                    | 4/4                | 3/4  | 2/4  | I <sub>I</sub> /I <sub>N</sub> | T <sub>I</sub> /T <sub>N</sub> | T <sub>B</sub> /T <sub>N</sub> |       |
| 400                                                  | Δ     | 50       | 2.20 | -/-   | 4.90 | 1425    | 14.7 | 79.7            | 80.3                                             | 78.1                   | 0.81               | 0.72 | 0.58 | 5.1                            | 2.3                            | 2.7                            | IE1   |
| 690                                                  | Y     | 50       | 2.20 | -/-   | 2.85 | 1425    | 14.7 | 79.7            | 80.3                                             | 78.1                   | 0.81               | 0.72 | 0.58 | 5.1                            | 2.3                            | 2.7                            | IE1   |
| 460                                                  | Δ     | 60       | 2.54 | -/-   | 4.70 | 1720    | 14.2 | 83.0            | 83.7                                             | 82.1                   | 0.82               | 0.75 | 0.62 | 5.8                            | 2.2                            | 2.4                            | IE1   |
|                                                      |       |          |      |       |      |         |      |                 |                                                  |                        |                    |      |      |                                |                                |                                |       |
| IM B5 / IM 3001                                      |       | FS 100 L |      | 18 kg |      | IP55    |      | IEC/EN 60034    |                                                  | IEC, DIN, ISO, VDE, EN |                    |      |      |                                |                                |                                |       |
| Environmental conditions : -20 °C - +40 °C / 1,000 m |       |          |      |       |      |         |      |                 | Locked rotor time (hot / cold) : 9.14 s   17.6 s |                        |                    |      |      |                                |                                |                                |       |

Mechanical data

|                                                                                     |                                 |                                 |                            |                                         |
|-------------------------------------------------------------------------------------|---------------------------------|---------------------------------|----------------------------|-----------------------------------------|
| Sound level (SPL / SWL) at 50Hz 60Hz                                                | 60.0 / 72.0 dB(A) <sup>2)</sup> | 62.0 / 74.0 dB(A) <sup>2)</sup> | External earthing terminal | No                                      |
| Moment of inertia                                                                   | 0.0059 kg m <sup>2</sup>        |                                 | Vibration severity grade   | A                                       |
| Bearing DE   NDE                                                                    | 6206 2Z C3                      | 6206 2Z C3                      | Insulation                 | 155(F) to 130(B)                        |
| bearing lifetime                                                                    |                                 |                                 | Duty type                  | S1                                      |
| L <sub>10mh</sub> F <sub>Rad min</sub> 50 60Hz <sup>1)</sup> for coupling operation | 40000 h                         | 32000 h                         | Direction of rotation      | bidirectional                           |
| Lubricants                                                                          | Unirex N3                       |                                 | Frame material             | aluminum                                |
| Regreasing device                                                                   | No                              |                                 | Coating (paint finish)     | Standard paint finish C2                |
| Grease nipple                                                                       | -/-                             |                                 | Color, paint shade         | RAL7030                                 |
| Type of bearing                                                                     | Preloaded bearing DE            |                                 | Motor protection           | (A) without (Standard)                  |
| Condensate drainage holes                                                           | -/-                             |                                 | Method of cooling          | IC411 - self ventilated, surface cooled |

Terminal box

|                          |           |                                |                     |
|--------------------------|-----------|--------------------------------|---------------------|
| Terminal box position    | top       | Max. cross-sectional area      | 4.0 mm <sup>2</sup> |
| Material of terminal box | Aluminium | Cable diameter from ... to ... | 11.0 mm - 21.0 mm   |
| Type of terminal box     | TB1 F00   | Cable entry                    | 2xM32x1,5           |
| Contact screw thread     | M4        | Cable gland                    | 2 plugs             |

Notes:

|                                                                         |                                           |                                                                  |
|-------------------------------------------------------------------------|-------------------------------------------|------------------------------------------------------------------|
| I <sub>A</sub> /I <sub>N</sub> = locked rotor current / current nominal | 1) L10mh according to DIN ISO 281 10/2010 | 3) Value is valid only for DOL operation with motor design IC411 |
| M <sub>K</sub> /M <sub>N</sub> = locked rotor torque / torque nominal   | 2) at rated power / at full load          |                                                                  |
| M <sub>B</sub> /M <sub>N</sub> = break down torque / nominal torque     |                                           |                                                                  |

|                                                                                    |                      |                 |             |                                                                                                              |                  |          |      |
|------------------------------------------------------------------------------------|----------------------|-----------------|-------------|--------------------------------------------------------------------------------------------------------------|------------------|----------|------|
| responsible dep.                                                                   | technical reference  | created by      | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                  |          |      |
| DI MC LVM                                                                          |                      | DT Configurator |             |                                                                                                              |                  |          |      |
|  | document type        |                 |             | document status                                                                                              |                  | customer |      |
|                                                                                    | datasheet            |                 |             | released                                                                                                     |                  |          |      |
|                                                                                    |                      | title           |             |                                                                                                              | document number  |          |      |
|                                                                                    | 1LE1002-1AB43-4FA4-Z |                 |             |                                                                                                              |                  |          |      |
|                                                                                    | D22                  |                 |             | rev.                                                                                                         | creation date    | language | Page |
| © Siemens AG 2021                                                                  |                      |                 |             | 01                                                                                                           | 2021-04-23 13:04 | en       | 1/2  |



**SIMOTICS GP - 100 L - IM B5 - 4p**

|     |                                                                                    |
|-----|------------------------------------------------------------------------------------|
| D22 | motor without CE character for export outside the EEA (see EU regulation 640/2009) |
|-----|------------------------------------------------------------------------------------|

Notes:

|                                                                                    |                               |                               |             |                                                                                                              |                                   |                |             |
|------------------------------------------------------------------------------------|-------------------------------|-------------------------------|-------------|--------------------------------------------------------------------------------------------------------------|-----------------------------------|----------------|-------------|
| responsible dep.<br>DI MC LVM                                                      | technical reference           | created by<br>DT Configurator | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                                   |                |             |
|  | document type<br>datasheet    |                               |             | document status<br>released                                                                                  |                                   | customer       |             |
|                                                                                    | title<br>1LE1002-1AB43-4FA4-Z |                               |             | document number                                                                                              |                                   |                |             |
| © Siemens AG 2021                                                                  | D22                           |                               |             | rev.<br>01                                                                                                   | creation date<br>2021-04-23 13:04 | language<br>en | Page<br>2/2 |