

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1112C

SIMOTICS GP - 112 M - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
230	Δ	50	2.20	-/-	9.90	940	22.5	77.7	78.4	76.6	0.72	0.64	0.51	4.6	2.6	2.7	IE1
400	Y	50	2.20	-/-	5.70	940	22.5	77.7	78.4	76.6	0.72	0.64	0.51	4.6	2.6	2.7	IE1
460	Y	60	2.54	-/-	5.60	1140	21.5	78.5	79.2	77.8	0.73	0.65	0.53	5.1	2.6	2.8	IE1
IM B3 / IM 1001			FS 112 M		25 kg		IP55	IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 14.4 s | 27.6 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	57.0 / 69.0 dB(A) ²⁾	60.0 / 72.0 dB(A) ²⁾	External earthing terminal	Yes
Moment of inertia	0.0092 kg m ²		Vibration severity grade	A
Bearing DE NDE	6206 2Z C3	6206 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	3 Bi-metallic sensors (opener) for tripping (2 terminals)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	4.0 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 F00	Cable entry	2xM32x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type	datasheet		document status	released		
	title	1LE1002-1BC22-2AZ4-Z B02+D22+F74+H04+Q3A		document number			
© Siemens AG 2021				rev.	creation date	language	Page
				01	2021-04-23 16:05	en	1/2

SIMOTICS GP - 112 M - IM B3 - 6p

B02	Acceptance test certificate 3.1 acc. to EN 10204	H04	External grounding at housing
D22	motor without CE character for export outside the EEA (see EU regulation 640/2009)	Q3A	1/3 Bi-metallic sensors (opener) for tripping (2 terminals)
F74	Sheet steel fan cowl		

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title			document number			
	1LE1002-1BC22-2AZ4-Z						
	B02+D22+F74+H04+Q3A			rev.	creation date	language	Page
© Siemens AG 2021				01	2021-04-23 16:05	en	2/2