

**SIMOTICS GP - 132 M - IM B3 - 6p**

|                  |                 |           |
|------------------|-----------------|-----------|
| Client order no. | Item-No.        | Offer no. |
| Order no.        | Consignment no. | Project   |

|         |
|---------|
| Remarks |
|---------|

## Safe Area

| U               | $\Delta / Y$ | f    | P        | P    | I     | n       | M    | $\eta^{3)}$ |      |              | $\cos\varphi^{3)}$ |                        |      | $I_A/I_N$ | $M_A/M_N$ | $M_K/M_N$ | IE-CL |
|-----------------|--------------|------|----------|------|-------|---------|------|-------------|------|--------------|--------------------|------------------------|------|-----------|-----------|-----------|-------|
| [V]             |              | [Hz] | [kW]     | [hp] | [A]   | [1/min] | [Nm] | 4/4         | 3/4  | 2/4          | 4/4                | 3/4                    | 2/4  | $I_A/I_N$ | $T_A/T_N$ | $T_B/T_N$ |       |
| 400             | $\Delta$     | 50   | 5.50     | -/-  | 12.70 | 955     | 55.0 | 83.1        | 84.0 | 82.8         | 0.75               | 0.67                   | 0.55 | 5.7       | 2.7       | 3.0       | IE1   |
| 690             | Y            | 50   | 5.50     | -/-  | 7.40  | 955     | 55.0 | 83.1        | 84.0 | 82.8         | 0.75               | 0.67                   | 0.55 | 5.7       | 2.7       | 3.0       | IE1   |
| 460             | $\Delta$     | 60   | 6.30     | -/-  | 12.20 | 1155    | 52.0 | 85.0        | 85.7 | 84.8         | 0.76               | 0.69                   | 0.57 | 6.2       | 2.7       | 3.1       | IE1   |
|                 |              |      |          |      |       |         |      |             |      |              |                    |                        |      |           |           |           |       |
| IM B3 / IM 1001 |              |      | FS 132 M |      | 48 kg |         | IP55 |             |      | IEC/EN 60034 |                    | IEC, DIN, ISO, VDE, EN |      |           |           |           |       |

Locked rotor time (hot / cold) : 11.4 s | 22.4 s

## Mechanical data

|                                                                                     |                                 |                                 |                            |                                         |
|-------------------------------------------------------------------------------------|---------------------------------|---------------------------------|----------------------------|-----------------------------------------|
| Sound level (SPL / SWL) at 50Hz 60Hz                                                | 63.0 / 75.0 dB(A) <sup>2)</sup> | 67.0 / 79.0 dB(A) <sup>2)</sup> | External earthing terminal | No                                      |
| Moment of inertia                                                                   | 0.0270 kg m <sup>2</sup>        |                                 | Vibration severity grade   | A                                       |
| Bearing DE   NDE                                                                    | 6208 2Z C3                      | 6208 2Z C3                      | Insulation                 | 155(F) to 130(B)                        |
| <b>bearing lifetime</b>                                                             |                                 |                                 | Duty type                  | S1                                      |
| L <sub>10mh</sub> F <sub>Rad min</sub> for coupling operation 50 60Hz <sup>1)</sup> | 40000 h                         | 32000 h                         | Direction of rotation      | bidirectional                           |
| Lubricants                                                                          | Unirex N3                       |                                 | Frame material             | aluminum                                |
| Regreasing device                                                                   | No                              |                                 | Coating (paint finish)     | Standard paint finish C2                |
| Grease nipple                                                                       | -/-                             |                                 | Color, paint shade         | RAL7030                                 |
| Type of bearing                                                                     | Preloaded bearing DE            |                                 | Motor protection           | (A) without (Standard)                  |
| Condensate drainage holes                                                           | -/-                             |                                 | Method of cooling          | IC411 - self ventilated, surface cooled |

## Terminal box

|                          |           |                                |                   |
|--------------------------|-----------|--------------------------------|-------------------|
| Terminal box position    | top       | Max. cross-sectional area      | 6.0 mm²           |
| Material of terminal box | Aluminium | Cable diameter from ... to ... | 11.0 mm - 21.0 mm |
| Type of terminal box     | TB1 H00   | Cable entry                    | 2xM32x1,5         |
| Contact screw thread     | M4        | Cable gland                    | 2 plugs           |

Notes:

$I_A/I_N$  = locked rotor current / current nominal  
 $M_A/M_N$  = locked rotor torque / torque nominal  
 $M_K/M_N$  = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010  
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

|                                                                                    |                     |                 |             |                                                                                                              |                  |          |      |
|------------------------------------------------------------------------------------|---------------------|-----------------|-------------|--------------------------------------------------------------------------------------------------------------|------------------|----------|------|
| responsible dep.                                                                   | technical reference | created by      | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                  |          |      |
| DI MC LVM                                                                          |                     | DT Configurator |             |                                                                                                              |                  |          |      |
|  | document type       |                 |             | document status                                                                                              |                  | customer |      |
|                                                                                    | datasheet           |                 |             | released                                                                                                     |                  |          |      |
|                                                                                    | title               |                 |             | document number                                                                                              |                  |          |      |
|                                                                                    | 1LE1002-1CC33-4AA4  |                 |             |                                                                                                              |                  |          |      |
| © Siemens AG 2021                                                                  |                     |                 |             | rev.                                                                                                         | creation date    | language | Page |
|                                                                                    |                     |                 |             | 01                                                                                                           | 2021-04-23 08:19 | en       | 1/1  |