

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1164B

SIMOTICS GP - 160 L - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
230	Δ	50	15.00	-/-	52.00	1460	98.0	88.7	89.0	87.8	0.82	0.76	0.63	7.5	3.0	3.6	IE1
400	Y	50	15.00	-/-	30.00	1460	98.0	88.7	89.0	87.8	0.82	0.76	0.63	7.5	3.0	3.6	IE1
460	Y	60	17.30	-/-	28.50	1755	94.0	90.5	90.9	89.8	0.84	0.79	0.68	8.0	2.9	3.6	IE1
IM B5 / IM 3001			FS 160 L		73 kg		IP65			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1,000 m										Locked rotor time (hot / cold) : 6.88 s 14 s							

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	65.0 / 77.0 dB(A) ²⁾	69.0 / 81.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0560 kg m ²		Vibration severity grade	A
Bearing DE NDE	6209 2Z C3	6209 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16.0 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J00	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
SIEMENS	document type datasheet			document status released		customer	
	title 1LE1002-1DB42-2FA4-Z			document number			
© Siemens AG 2021	D22+H07+H20+N30			rev. 01	creation date 2021-04-22 12:16	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1164B

SIMOTICS GP - 160 L - IM B5 - 4p

Special design

D22	motor without CE character for export outside the EEA (see EU regulation 640/2009)	H20	IP 65 degree of protection
H07	Stainless steel screws and bolts (outside the motor)	N30	Increased air humidity/temperature with 30 to 60 g water per m3 air

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1002-1DB42-2FA4-Z	document number						
© Siemens AG 2021	D22+H07+H20+N30	rev. 01	creation date 2021-04-22 12:16		language en	Page 2/2		