

SIMOTICS GP - 71 M - IM B14 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

-/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
220	Δ	50	0.55	-/-	2.45	2850	1.8	77.8	77.5	74.5	0.76	0.67	0.54	6.1	3.7	3.7	IE3
380	Y	50	0.55	-/-	1.41	2850	1.8	77.8	77.5	74.5	0.76	0.67	0.54	6.1	3.7	3.7	IE3
440	Y	60	0.63	-/-	1.42	3450	1.7	76.8	76.1	72.9	0.76	0.68	0.55	6.6	3.9	3.9	IE3
440	Y	60	0.55	-/-	1.29	3470	1.5	76.8	75.3	71.0	0.73	0.64	0.51	7.2	4.5	4.5	IE3
IM B14 / IM 3601			FS 71 M			IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 22.9 s | 28.9 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	57 / 68 dB(A) ^{2) 3)}	62 / 73 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0006 kg m²		Thermal class	F
Bearing DE NDE	6202 2Z C3	6202 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	8 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(A) without (Standard)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 B00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents 	
	document type datasheet			document status released			
	title 1LE1003-0CA32-1KA4-Z			document number			
© INNOMOTICS 2023	L21			rev. 950	creation date 2023-09-30	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3073A

SIMOTICS GP - 71 M - IM B14 - 2p

Special design

L21 Locating (fixed) bearing, NDE

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents			
	document type datasheet				document status released			
	title 1LE1003-0CA32-1KA4-Z				document number			
© INNOMOTICS 2023	L21				rev. 950	creation date 2023-09-30	language en	Page 2/2