

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3082A

SIMOTICS GP - 80 M - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	0.75	-/-	2.70	2850	2.5	80.7	82.2	81.9	0.86	0.82	0.73	6.2	2.6	3.0	IE3
400	Y	50	0.75	-/-	1.56	2850	2.5	80.7	82.2	81.9	0.86	0.82	0.73	6.2	2.6	3.0	IE3
460	Y	60	0.86	-/-	1.63	3450	2.4	77.0	78.0	77.2	0.86	0.82	0.73	6.4	2.6	3.1	IE3
460	Y	60	0.75	-/-	1.45	3480	2.0	77.0	77.2	75.7	0.84	0.79	0.70	7.1	3.0	3.6	IE3
IM B3 / IM 1001			FS 80 M			IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 21.1 s 27.7 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	60 / 71 dB(A) ²⁾	64 / 75 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.0011 kg m ²		Thermal class	F
Bearing DE NDE	6004 2Z C3	6004 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad} min 50 60Hz Lubricants	40000 h	32000 h	Frame material	aluminum
Regreasing device	No		Net weight of the motor (IM B3)	11 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	No		Motor protection	(A) without (Standard)
External earthing terminal	No		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _A /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _K /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type	datasheet			document status		
					released		
	title	1LE1003-0DA22-2AA4-Z			document number		
	F74+M11						
© Siemens AG 2021		rev.	creation date	language	Page		
		01	2021-12-07	en	1/2		

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3082A

SIMOTICS GP - 80 M - IM B3 - 2p

Special design

F74 Sheet steel fan cowl M11 Stainless steel rating plate

Notes:

responsible dep.

DI MC LVM

technical reference

created by

DT Configurator

approved by

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

[Link documents](#)

SIEMENS

document type

datasheet

title

1LE1003-0DA22-2AA4-Z

F74+M11

document status

released

document number

rev.

01

creation date

2021-12-07

language

en

Page

2/2