

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3083B

SIMOTICS GP - 80 M - IM B14 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\phi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL	
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N		
DOL duty (S1) - 155(F) to 130(B)																		
IM B14 / IM 3601			FS 80 M			IP55		UKCA		IEC/EN 60034			IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - + °C / m									Locked rotor time (hot / cold) : 19.8 s 23.6 s									

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	53 / 64 dB(A) ^{2) 3)}	53 / 64 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0029 kg m ²		Thermal class	F
Bearing DE NDE			Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L_{10mh} , $F_{Rad min}$ for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Regreasing device	No		Net weight of the motor (IM B3)	14 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	No		Motor protection	(A) without (Standard)
External earthing terminal	No		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I_A/I_N = locked rotor current / current nominal 1) L10mh according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411
 M_A/M_N = locked rotor torque / torque nominal 2) at rated power / at full load

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents 
	document type datasheet	document status released			
	title 1LE1003-0DB39-0KA4-Z B02+M1Y+Y50	document number			
© Siemens AG 2022	rev. 929	creation date 2022-12-01	language en	Page 1/2	

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3083B

SIMOTICS GP - 80 M - IM B14 - 4p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	Y50	Temperature class 155(F), utilized acc. to 130(B), customer indication of coolant temperature and/or installation altitude
M1Y	Non-standard winding:		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
SIEMENS	document type datasheet	document status released			
	title 1LE1003-0DB39-0KA4-Z B02+M1Y+Y50	document number			
© Siemens AG 2022	rev. 929	creation date 2022-12-01	language en	Page 2/2	