

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3094B SIMOTICS GP - 90 L - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	1.50	-/-	5.50	1445	9.9	85.3	85.7	84.4	0.80	0.73	0.60	7.3	2.9	3.5	IE3
400	Y	50	1.50	-/-	3.15	1445	9.9	85.3	85.7	84.4	0.80	0.73	0.60	7.3	2.9	3.5	IE3
460	Y	60	1.75	-/-	3.15	1740	9.6	86.5	86.7	85.4	0.80	0.74	0.62	7.7	2.9	3.7	IE3
460	Y	60	1.50	-/-	2.85	1755	8.2	86.5	86.6	84.7	0.77	0.69	0.57	8.6	3.4	4.3	IE3
IM B5 / IM 3001		FS 90 L				IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 17.3 s 21.5 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	56 / 68 dB(A) ^{2) 3)}	58 / 70 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0049 kg m ²		Thermal class	F
Bearing DE NDE	6205 2Z C3	6004 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	19 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(A) without (Standard)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes: I_A/I_N = locked rotor current / current nominal 1) L10mh according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411
M_K/M_N = locked rotor torque / torque nominal 2) at rated power / at full load
M_K/M_N = break down torque / nominal torque

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
SIEMENS	document type datasheet				document status released
	title 1LE1003-0EB42-2FA4-Z B02				document number
© Siemens AG 2023				rev. 943	creation date 2023-05-09
				language en	Page 1/2



Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3094B

SIMOTICS GP - 90 L - IM B5 - 4p

Special design

B02

Acceptance test certificate 3.1 acc. to EN 10204

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet			document status released	
	title 1LE1003-0EB42-2FA4-Z			document number	
© Siemens AG 2023	B02			rev. 943	creation date 2023-05-09
				language en	Page 2/2

