

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3094B

SIMOTICS GP - 90 L - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
400	Δ	50	1.50	-/-	3.15	1445	9.9	85.3	86.0	85.2	0.80	0.73	0.60	7.3	2.9	3.5	IE3
690	Y	50	1.50	-/-	1.84	1445	9.9	85.3	86.0	85.2	0.80	0.73	0.60	7.3	2.9	3.5	IE3
460	Δ	60	1.75	-/-	3.15	1740	9.6	86.5	87.0	85.7	0.80	0.74	0.62	7.7	2.9	3.7	IE3
460	Δ	60	1.50	-/-	2.85	1755	8.2	86.5	86.2	84.5	0.77	0.69	0.57	8.6	3.4	4.3	IE3

IM B5 / IM 3001		FS 90 L	19 kg	IP65		IEC/EN 60034	IEC, DIN, ISO, VDE, EN		
-----------------	--	---------	-------	------	--	--------------	------------------------	--	--

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 17.9 s | 21.8 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	56.0 / 68.0 dB(A) ²⁾	58.0 / 70.0 dB(A) ²⁾	External earthing terminal	Yes
Moment of inertia	0.0049 kg m ²		Vibration severity grade	A
Bearing DE NDE	6205 2Z C3	6004 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing DE		Motor protection	(B) 1 PTC thermistor - for tripping (2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9.0 mm - 17.0 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_K/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

¹⁾ L10mh according to DIN ISO 281 10/2010
²⁾ at rated power / at full load

³⁾ Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number		
	1LE1003-0EB43-4FB4-Z B02+H04+H20+L20+N30+Y82			
© Siemens AG 2021	rev.	creation date	language	Page
	01	2021-04-22 10:15	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3094B

SIMOTICS GP - 90 L - IM B5 - 4p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	L20	Locating bearing, DE
H04	External grounding at housing	N30	Increased air humidity/temperature with 30 to 60 g water per m3 air
H20	IP 65 degree of protection	Y82	Auxiliary name plate with customer data

Notes:

responsible dep. DI MC LVM		technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.				
		document type datasheet			document status released		customer		
		title 1LE1003-0EB43-4FB4-Z			document number				
© Siemens AG 2021		B02+H04+H20+L20+N30+Y82			rev. 01	creation date 2021-04-22 10:15		language en	Page 2/2