

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3104A

SIMOTICS GP - 100 L - IM B5 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL	
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N		
DOL duty (S1) - 155(F) to 155(F)																		
400	Δ	50	3.00	-/-	5.70	2910	9.8	87.1	87.7	87.0	0.87	0.82	0.72	9.4	4.4	4.5	IE3	
690	Y	50	3.00	-/-	3.30	2910	9.8	87.1	87.7	87.0	0.87	0.82	0.72	9.4	4.4	4.5	IE3	
460	Δ	60	3.45	-/-	5.60	3505	9.4	88.5	88.5	87.5	0.87	0.83	0.73	10.0	4.0	4.8	IE3	
460	Δ	60	3.00	-/-	5.00	3525	8.1	88.5	88.2	86.7	0.85	0.80	0.69	11.2	4.6	5.6	IE3	
IM B5 / IM 3001			FS 100 L				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - + °C / 1,000 m									Locked rotor time (hot / cold) : 9 s 12 s									

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	67 / 79 dB(A) ²⁾	71 / 83 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.0041 kg m ²		Thermal class	F
Bearing DE NDE	6206 2Z C3	6206 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad} min 50 60Hz	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	25 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	4 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 F00	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _A /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _K /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type				document status		
	datasheet				released		
	title				document number		
	1LE1003-1AA43-4FA4-Z						
© Siemens AG 2022	N03				rev.	creation date	language
					01	2022-03-15	en
						Page	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3104A

SIMOTICS GP - 100 L - IM B5 - 2p

Special design

N03 Temperature class 155 (F), utilised to 155 (F), with increased cooling medium temperature

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				document status released
	title 1LE1003-1AA43-4FA4-Z				document number
© Siemens AG 2022	N03				rev. 01
					creation date 2022-03-15
		language en	Page 2/2		

