

SIMOTICS GP - 100 L - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_I/I_N	T_I/T_N	T_B/T_N	
220	Δ	50		-/-		1465	14.3	86.7	87.3	86.4	0.83	0.77	0.66	7.6	2.1	3.6	IE3
380	Y	50		-/-		1465	14.3	86.7	87.3	86.4	0.83	0.77	0.66	7.6	2.1	3.6	IE3
IM B5 / IM 3001			FS 100 L		30 kq		IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					

Locked rotor time (hot / cold) : 11.7 s | 15.1 s

Sound level (SPL / SWL) at 50Hz 60Hz	60.0 / 72.0 dB(A) ²⁾	62.0 / 74.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0140 kg m ²		Vibration severity grade	A
Bearing DE NDE	6206 2Z C3	6206 2Z C3	Insulation	155(F) to 155(F)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	3 Bi-metallic sensors (opener) for tripping (2 terminals)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box position	top	Max. cross-sectional area	4.0 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 F10	Cable entry	Han-Drive 10e
Contact screw thread	M4	Cable gland	connector

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title			document number			
	1LE1003-1AB42-1FZ4-Z						
	M10+Q3A+R70+Y52			rev.	creation date	language	Page
© Siemens AG 2021				01	2021-04-20 23:09	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3104B

SIMOTICS GP - 100 L - IM B5 - 4p

Special design

M10	Additional rating plate, loose	R70	Motor connector Han-Drive 10e for 230 VD/400 VY
Q3A	1/3 Bi-metallic sensors (opener) for tripping (2 terminals)	Y52	Temperature class 155(F), utilized acc. to 155(F), customer indication of coolant temperature and/or installation altitude

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet				document status released		customer	
	title 1LE1003-1AB42-1FZ4-Z M10+Q3A+R70+Y52				document number			
© Siemens AG 2021				rev. 01	creation date 2021-04-20 23:09	language en	Page 2/2	