

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3104B

SIMOTICS GP - 100 L - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
380	Δ	50	2.52	-/-	5.20	1445	16.6	86.4	87.6	87.3	0.85	0.81	0.71	7.2	2.6	3.3	IE3
660	Y	50	2.52	-/-	3.00	1445	16.6	86.4	87.6	87.3	0.85	0.81	0.71	7.2	2.6	3.3	IE3
440	Δ	60	2.93	-/-	5.00	1740	16.1	89.1	90.5	90.3	0.87	0.82	0.73	7.7	2.6	3.4	IE3
440	Δ	60	2.20	-/-	4.05	1760	11.9	89.5	89.5	88.0	0.80	0.73	0.61	9.9	3.5	4.6	IE3
IM B5 / IM 3001		FS 100 L		30 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 18.6 s | 22.6 s

These values are calculated. The final rating plate data will be calculated when the order is placed

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	59.0 / 63.0 dB(A) ²⁾	59.0 / 63.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0101 kg m ²		Vibration severity grade	A
Bearing DE NDE	6206 2Z C3	6206 2Z C3	Insulation	155(F) to 155(F)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	Yes		Method of cooling	IC416 - separately ventilated, surface cooled

Terminal box

Terminal box position	right	Max. cross-sectional area	4.0 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 F00	Cable entry	2xM32x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title			document number			
	1LE1003-1AB43-3FB5-Z						
© Siemens AG 2021	F01+F12+F70+H03+N02			rev.	creation date	language	Page
				01	2021-05-28 10:03	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3104B

SIMOTICS GP - 100 L - IM B5 - 4p

Special design

F01	Mounting a brake	H03	Condensation drain holes in end shield
F12	Brake supply voltage 400 V AC, 50/60 Hz	N02	Temperature class 155 (F), utilised to 155 (F), with increased power
F70	Mounting of separately driven fan		

Additional information:

Brake:

Description:	BFK458-12	Current:	.22 A
Voltage:	AC 400 V	Moment of inertia:	.00036 Nm

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1003-1AB43-3FB5-Z			document number				
© Siemens AG 2021	F01+F12+F70+H03+N02			rev. 01	creation date 2021-05-28 10:03	language en	Page 2/2	