



**SIMOTICS GP - 100 L - IM B5 - 4p**

|                  |                 |           |
|------------------|-----------------|-----------|
| Client order no. | Item-No.        | Offer no. |
| Order no.        | Consignment no. | Project   |

|         |
|---------|
| Remarks |
|---------|

## Safe Area

| U               | $\Delta / Y$ | f    | P        | P    | I     | n       | M    | $\eta^{3)}$ |      |              | $\cos\varphi^{3)}$ |                        |      | $I_A/I_N$ | $M_A/M_N$ | $M_K/M_N$ | IE-CL |
|-----------------|--------------|------|----------|------|-------|---------|------|-------------|------|--------------|--------------------|------------------------|------|-----------|-----------|-----------|-------|
| [V]             |              | [Hz] | [kW]     | [hp] | [A]   | [1/min] | [Nm] | 4/4         | 3/4  | 2/4          | 4/4                | 3/4                    | 2/4  | $I_A/I_N$ | $T_A/T_N$ | $T_B/T_N$ |       |
| 400             | $\Delta$     | 50   | 2.20     | -/-  | 4.40  | 1465    | 14.3 | 86.7        | 87.3 | 86.4         | 0.83               | 0.77                   | 0.66 | 7.6       | 2.1       | 3.6       | IE3   |
| 690             | Y            | 50   | 2.20     | -/-  | 2.55  | 1465    | 14.3 | 86.7        | 87.3 | 86.4         | 0.83               | 0.77                   | 0.66 | 7.6       | 2.1       | 3.6       | IE3   |
| 460             | $\Delta$     | 60   | 2.54     | -/-  | 4.35  | 1760    | 13.8 | 87.5        | 87.9 | 87.1         | 0.84               | 0.79                   | 0.68 | 7.7       | 2.2       | 3.7       | IE2   |
| 460             | $\Delta$     | 60   | 2.20     | -/-  | 3.90  | 1770    | 11.9 | 87.5        | 87.4 | 85.8         | 0.81               | 0.75                   | 0.63 | 8.7       | 2.5       | 4.3       | IE2   |
| IM B5 / IM 3001 |              |      | FS 100 L |      | 30 kq |         | IP55 |             |      | IEC/EN 60034 |                    | IEC, DIN, ISO, VDE, EN |      |           |           |           |       |

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 11.7 s | 15.1 s

## Mechanical data

|                                                                                     |                                 |                                 |                            |                                                    |
|-------------------------------------------------------------------------------------|---------------------------------|---------------------------------|----------------------------|----------------------------------------------------|
| Sound level (SPL / SWL) at 50Hz 60Hz                                                | 60.0 / 72.0 dB(A) <sup>2)</sup> | 62.0 / 74.0 dB(A) <sup>2)</sup> | External earthing terminal | No                                                 |
| Moment of inertia                                                                   | 0.0140 kg m²                    |                                 | Vibration severity grade   | A                                                  |
| Bearing DE   NDE                                                                    | 6206 2Z C3                      | 6206 2Z C3                      | Insulation                 | 155(F) to 130(B)                                   |
| bearing lifetime                                                                    |                                 |                                 | Duty type                  | S1                                                 |
| L <sub>10mh</sub> F <sub>Rad min</sub> for coupling operation 50 60Hz <sup>1)</sup> | 40000 h                         | 32000 h                         | Direction of rotation      | bidirectional                                      |
| Lubricants                                                                          | Unirex N3                       |                                 | Frame material             | aluminum                                           |
| Regreasing device                                                                   | No                              |                                 | Coating (paint finish)     | Standard paint finish C2                           |
| Grease nipple                                                                       | -/-                             |                                 | Color, paint shade         | RAL7030                                            |
| Type of bearing                                                                     | Preloaded bearing DE            |                                 | Motor protection           | (B) 3 PTC thermistors - for tripping (2 terminals) |
| Condensate drainage holes                                                           | No                              |                                 | Method of cooling          | IC411 - self ventilated, surface cooled            |

## Terminal box

|                          |           |                                |                     |
|--------------------------|-----------|--------------------------------|---------------------|
| Terminal box position    | top       | Max. cross-sectional area      | 4.0 mm²             |
| Material of terminal box | Aluminium | Cable diameter from ... to ... | 11.0 mm - 21.0 mm   |
| Type of terminal box     | TB1 F00   | Cable entry                    | 2xM32x1,5-1xM16x1,5 |
| Contact screw thread     | M4        | Cable gland                    | 3 plugs             |

Notes:

$I_A/I_N$  = locked rotor current / current nominal  
 $M_A/M_N$  = locked rotor torque / torque nominal  
 $M_K/M_N$  = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010  
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

|                                                                                    |                     |                 |             |                                                                                                              |                  |          |      |
|------------------------------------------------------------------------------------|---------------------|-----------------|-------------|--------------------------------------------------------------------------------------------------------------|------------------|----------|------|
| responsible dep.                                                                   | technical reference | created by      | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                  |          |      |
| DI MC LVM                                                                          |                     | DT Configurator |             |                                                                                                              |                  |          |      |
|  | document type       |                 |             | document status                                                                                              |                  | customer |      |
|                                                                                    | datasheet           |                 |             | released                                                                                                     |                  |          |      |
|                                                                                    | title               |                 |             | document number                                                                                              |                  |          |      |
|                                                                                    | 1LE1003-1AB43-4FB4  |                 |             |                                                                                                              |                  |          |      |
| © Siemens AG 2021                                                                  |                     |                 |             | rev.                                                                                                         | creation date    | language | Page |
|                                                                                    |                     |                 |             | 01                                                                                                           | 2021-05-06 09:50 | en       | 1/1  |