



**SIMOTICS GP - 100 L - IM V18 - 4p**

|                  |                 |           |
|------------------|-----------------|-----------|
| Client order no. | Item-No.        | Offer no. |
| Order no.        | Consignment no. | Project   |

|         |
|---------|
| Remarks |
|---------|

## Safe Area

-/-

| U                                                    | Δ / Y | f    | P        | P    | I     | n       | M    | η <sup>3)</sup> |                                                  |                        | cosφ <sup>3)</sup> |      |      | I <sub>A</sub> /I <sub>N</sub> | M <sub>A</sub> /M <sub>N</sub> | M <sub>K</sub> /M <sub>N</sub> | IE-CL |
|------------------------------------------------------|-------|------|----------|------|-------|---------|------|-----------------|--------------------------------------------------|------------------------|--------------------|------|------|--------------------------------|--------------------------------|--------------------------------|-------|
| [V]                                                  |       | [Hz] | [kW]     | [hp] | [A]   | [1/min] | [Nm] | 4/4             | 3/4                                              | 2/4                    | 4/4                | 3/4  | 2/4  | I <sub>I</sub> /I <sub>N</sub> | T <sub>I</sub> /T <sub>N</sub> | T <sub>B</sub> /T <sub>N</sub> |       |
| <b>DOL duty (S1) - 155(F) to 130(B)</b>              |       |      |          |      |       |         |      |                 |                                                  |                        |                    |      |      |                                |                                |                                |       |
| 230                                                  | Δ     | 50   | 3.00     | -/-  | 10.70 | 1450    | 19.8 | 87.7            | 88.1                                             | 87.1                   | 0.80               | 0.73 | 0.60 | 8.0                            | 3.1                            | 3.8                            | IE3   |
| 400                                                  | Y     | 50   | 3.00     | -/-  | 6.20  | 1450    | 19.8 | 87.7            | 88.1                                             | 87.1                   | 0.80               | 0.73 | 0.60 | 8.0                            | 3.1                            | 3.8                            | IE3   |
| 460                                                  | Y     | 60   | 3.45     | -/-  | 6.10  | 1750    | 18.8 | 87.5            | 88.0                                             | 87.2                   | 0.81               | 0.74 | 0.62 | 9.0                            | 3.1                            | 4.1                            | IE2   |
| 460                                                  | Y     | 60   | 3.00     | -/-  | 5.40  | 1760    | 16.3 | 89.5            | 89.4                                             | 88.0                   | 0.78               | 0.70 | 0.58 | 9.9                            | 3.5                            | 4.7                            | IE3   |
| IM V18 / IM 3611                                     |       |      | FS 100 L |      |       | IP55    | UKCA | IEC/EN 60034    |                                                  | IEC, DIN, ISO, VDE, EN |                    |      |      |                                |                                |                                |       |
| Environmental conditions : -20 °C - +40 °C / 1,000 m |       |      |          |      |       |         |      |                 | Locked rotor time (hot / cold) : 12.8 s   17.6 s |                        |                    |      |      |                                |                                |                                |       |

## Mechanical data

|                                                                                        |                                |                                |                                 |                                                             |
|----------------------------------------------------------------------------------------|--------------------------------|--------------------------------|---------------------------------|-------------------------------------------------------------|
| Sound level (SPL / SWL) at 50Hz 60Hz                                                   | 67 / 75 dB(A) <sup>2) 3)</sup> | 70 / 78 dB(A) <sup>2) 3)</sup> | Vibration severity grade        | A                                                           |
| Moment of inertia                                                                      | 0.0100 kg m²                   |                                | Thermal class                   | F                                                           |
| Bearing DE   NDE                                                                       | 6206 2Z C3                     | 6206 2Z C3                     | Duty type                       | S1                                                          |
| <b>bearing lifetime</b>                                                                |                                |                                | Direction of rotation           | bidirectional                                               |
| L <sub>10mh</sub> F <sub>Rad min</sub> for coupling operation<br>50 60Hz <sup>1)</sup> | 20000 h                        | 16000 h                        | Frame material                  | aluminum                                                    |
| Regreasing device                                                                      | Without                        |                                | Net weight of the motor (IM B3) | 26 kg                                                       |
| Grease nipple                                                                          | -/-                            |                                | Coating (paint finish)          | Standard paint finish C2                                    |
| Type of bearing                                                                        | Preloaded bearing DE           |                                | Color, paint shade              | RAL7030                                                     |
| Condensate drainage holes                                                              | Without                        |                                | Motor protection                | 1/3 Bi-metallic sensors (opener) for tripping (2 terminals) |
| External earthing terminal                                                             | Without                        |                                | Method of cooling               | IC411 - self ventilated, surface cooled                     |

## Terminal box

|                          |           |                                |                     |
|--------------------------|-----------|--------------------------------|---------------------|
| Terminal box position    | top       | Max. cross-sectional area      | 4 mm²               |
| Material of terminal box | Aluminium | Cable diameter from ... to ... | 11 mm - 21 mm       |
| Type of terminal box     | TB1 F00   | Cable entry                    | 2xM32x1,5-1xM16x1,5 |
| Contact screw thread     | M4        | Cable gland                    | 3 plugs             |

Notes:

$I_A/I_N$  = locked rotor current / current nominal  
 $M_A/M_N$  = locked rotor torque / torque nominal  
 $M_K/M_N$  = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010  
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

|                                                                                    |                                              |                   |             |                                                                                                              |                             |                                                                                                                         |             |
|------------------------------------------------------------------------------------|----------------------------------------------|-------------------|-------------|--------------------------------------------------------------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------------------------------------------|-------------|
| responsible dep.<br>IN LVM                                                         | technical reference                          | created by<br>SPC | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                             | <a href="#">Link documents</a><br> |             |
|  | document type<br>datasheet                   |                   |             | document status<br>released                                                                                  |                             |                                    |             |
|                                                                                    | title<br>1LE1003-1AB52-2MZ4-Z<br>H00+P01+Q3A |                   |             | document number                                                                                              |                             |                                                                                                                         |             |
| © INNOMOTICS 2023                                                                  |                                              |                   |             | rev.<br>951                                                                                                  | creation date<br>2023-11-02 | language<br>en                                                                                                          | Page<br>1/2 |

### Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3105B

**SIMOTICS GP - 100 L - IM V18 - 4p**

## Special design

|     |                             |     |                                                             |
|-----|-----------------------------|-----|-------------------------------------------------------------|
| H00 | Canopy                      | Q3A | 1/3 Bi-metallic sensors (opener) for tripping (2 terminals) |
| P01 | Next larger standard flange |     |                                                             |

**Notes:**

|                            |                               |                   |             |                                                                                                              |                             |                                                                                       |             |
|----------------------------|-------------------------------|-------------------|-------------|--------------------------------------------------------------------------------------------------------------|-----------------------------|---------------------------------------------------------------------------------------|-------------|
| responsible dep.<br>IN LVM | technical reference           | created by<br>SPC | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                             | <a href="#">Link documents</a>                                                        |             |
| SIEMENS                    | document type<br>datasheet    |                   |             | document status<br>released                                                                                  |                             |  |             |
|                            | title<br>1LE1003-1AB52-2MZ4-Z |                   |             | document number                                                                                              |                             |                                                                                       |             |
| © INNOMOTICS 2023          | H00+P01+Q3A                   |                   |             | rev.<br>951                                                                                                  | creation date<br>2023-11-02 | language<br>en                                                                        | Page<br>2/2 |