

SIMOTICS GP - 100 L - IM V1 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	1.50	-/-	6.30	970	14.8	82.5	83.1	81.5	0.73	0.65	0.52	5.2	1.9	2.8	IE3
400	Y	50	1.50	-/-	3.60	970	14.8	82.5	83.1	81.5	0.73	0.65	0.52	5.2	1.9	2.8	IE3
IM V1 / IM 3011			FS 100 L			IP65	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 26.6 s 34.7 s								

Sound level (SPL / SWL) at 50Hz 60Hz	59 / 71 dB(A) ^{2) 3)}	62 / 74 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0110 kg m²		Thermal class	F
Bearing DE NDE	6206 2Z C3	6206 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	20000 h	16000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	25 kg
Regreasing device	No		Coating (paint finish)	Special paint finish, resistant to salt-laden air C4
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	Yes			

Terminal box position	top	Max. cross-sectional area	4 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 F00	Cable entry	2xM32x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1003-1AC42-2GA4-Z						
	B07+B99+H04+H20+N31+Q02+S03+Y66			rev.	creation date	language	Page
© Siemens AG 2022				929	2022-11-24	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3104C

SIMOTICS GP - 100 L - IM V1 - 6p

Special design

B07	Supplementary plate, voltage tolerance	N31	Increased air humidity/temperature with 60 to 100 g water per m3 air
B99	Lattice pallet packaging	Q02	Anti-condensation heating for 230 V (2 terminals)
H04	External grounding at housing	S03	Special paint finish in sea air resistant C4
H20	IP 65 degree of protection	Y66	Non-standard colors

Additional information:

Space heaters

Technical data: 1-phase, 230 V 25W

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				document status released
	title 1LE1003-1AC42-2GA4-Z B07+B99+H04+H20+N31+Q02+S03+Y66				document number
© Siemens AG 2022		rev. 929	creation date 2022-11-24	language en	Page 2/2

