

# Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3112B

SIMOTICS GP - 112 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

## Electrical data

## Safe Area

U [V]	$\Delta / Y$	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	$\eta$ <sup>3)</sup>			$\cos\phi$ <sup>3)</sup>			$I_A/I_N$ $I_i/I_N$	$M_A/M_N$ $T_i/T_N$	$M_K/M_N$ $T_B/T_N$	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
240	$\Delta$	50	4.00	-/-	13.20	1460	26.0	88.6	89.2	88.6	0.82	0.76	0.65	7.1	2.4	3.7	IE3
415	Y	50	4.00	-/-	7.70	1460	26.0	88.6	89.2	88.6	0.82	0.76	0.65	7.1	2.4	3.7	IE3
480	Y	60	4.55	-/-	7.40	1760	24.5	89.5	90.0	89.3	0.83	0.78	0.67	7.3	2.5	3.8	IE3
480	Y	60	3.70	-/-	6.20	1770	20.0	89.5	89.4	87.7	0.80	0.73	0.61	8.2	2.9	4.3	IE3
IM B3 / IM 1001			FS 112 M		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN								
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 16 s   21.7 s								

## Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	58 / 70 dB(A) <sup>2)</sup>	62 / 74 dB(A) <sup>2)</sup>	Vibration severity grade	A
Moment of inertia	0.0170 kg m <sup>2</sup>		Insulation	155(F) to 130(B)
Bearing DE   NDE	6206 2Z C3	6206 2Z C3	Duty type	S1
<b>bearing lifetime</b>			Direction of rotation	bidirectional
L <sub>10mh</sub> , F <sub>Rad</sub> min 50 60Hz <sup>1)</sup> for coupling operation	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	34 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing DE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

## Terminal box

Terminal box position	top	Max. cross-sectional area	4 mm <sup>2</sup>
Material of terminal box	Aluminium	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 F00	Cable entry	2xM32x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	3 plugs

## Notes:

$I_A/I_N$  = locked rotor current / current nominal  
 $M_K/M_N$  = locked rotor torque / torque nominal  
 $M_i/M_N$  = break down torque / nominal torque  
 1) L10mh according to DIN ISO 281 10/2010  
 2) at rated power / at full load  
 3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>			
<b>SIEMENS</b>	document type datasheet	document status released		customer			
	title 1LE1003-1BB22-3AB4-Z B02+F74+F76+L20	document number					
© Siemens AG 2021	rev. 01	creation date 2021-11-15 17:04	language en	Page 1/2			

**Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS**



Motor type : 1AV3112B

SIMOTICS GP - 112 M - IM B3 - 4p

**Special design**

B02	Acceptance test certificate 3.1 acc. to EN 10204	F76	Metal external fan
F74	Sheet steel fan cowl	L20	Locating bearing, DE

**Notes:**

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>
-------------------------------	---------------------	-------------------------------	-------------	---

<b>SIEMENS</b>	document type datasheet	document status released	customer			
	title 1LE1003-1BB22-3AB4-Z B02+F74+F76+L20	document number	rev. 01	creation date 2021-11-15 17:04	language en	Page 2/2
© Siemens AG 2021						