

**SIMOTICS GP - 112 M - IM B5 - 4p**

|                  |                 |           |
|------------------|-----------------|-----------|
| Client order no. | Item-No.        | Offer no. |
| Order no.        | Consignment no. | Project   |

|         |
|---------|
| Remarks |
|---------|

## Safe Area

| U               | Δ / Y | f    | P        | P    | I     | n       | M    | η <sup>3)</sup> |      |              | cosφ <sup>3)</sup> |                        |      | I <sub>A</sub> /I <sub>N</sub> | M <sub>A</sub> /M <sub>N</sub> | M <sub>K</sub> /M <sub>N</sub> | IE-CL |
|-----------------|-------|------|----------|------|-------|---------|------|-----------------|------|--------------|--------------------|------------------------|------|--------------------------------|--------------------------------|--------------------------------|-------|
| [V]             |       | [Hz] | [kW]     | [hp] | [A]   | [1/min] | [Nm] | 4/4             | 3/4  | 2/4          | 4/4                | 3/4                    | 2/4  | I <sub>I</sub> /I <sub>N</sub> | T <sub>I</sub> /T <sub>N</sub> | T <sub>B</sub> /T <sub>N</sub> |       |
| 400             | Δ     | 50   | 4.00     | -/-  | 7.90  | 1460    | 26.0 | 88.6            | 89.2 | 88.6         | 0.82               | 0.76                   | 0.65 | 7.1                            | 2.4                            | 3.7                            | IE3   |
| 690             | Y     | 50   | 4.00     | -/-  | 4.60  | 1460    | 26.0 | 88.6            | 89.2 | 88.6         | 0.82               | 0.76                   | 0.65 | 7.1                            | 2.4                            | 3.7                            | IE3   |
| 460             | Δ     | 60   | 4.55     | -/-  | 7.70  | 1760    | 24.5 | 89.5            | 90.0 | 89.3         | 0.83               | 0.78                   | 0.67 | 7.3                            | 2.5                            | 3.8                            | IE3   |
| 460             | Δ     | 60   | 3.70     | -/-  | 6.50  | 1770    | 20.0 | 89.5            | 89.4 | 87.7         | 0.80               | 0.73                   | 0.61 | 8.2                            | 2.9                            | 4.3                            | IE3   |
| IM B5 / IM 3001 |       |      | FS 112 M |      | 34 kq |         | IP55 |                 |      | IEC/EN 60034 |                    | IEC, DIN, ISO, VDE, EN |      |                                |                                |                                |       |

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 16 s | 21.7 s

|                                                                                        |                                 |                                 |                            |                                                    |
|----------------------------------------------------------------------------------------|---------------------------------|---------------------------------|----------------------------|----------------------------------------------------|
| Sound level (SPL / SWL) at 50Hz 60Hz                                                   | 58.0 / 70.0 dB(A) <sup>2)</sup> | 62.0 / 74.0 dB(A) <sup>2)</sup> | External earthing terminal | No                                                 |
| Moment of inertia                                                                      | 0.0170 kg m <sup>2</sup>        |                                 | Vibration severity grade   | A                                                  |
| Bearing DE   NDE                                                                       | 6206 2Z C3                      | 6206 2Z C3                      | Insulation                 | 155(F) to 130(B)                                   |
| <b>bearing lifetime</b>                                                                |                                 |                                 | Duty type                  | S1                                                 |
| L <sub>10mh</sub> F <sub>Rad min</sub> for coupling operation<br>50 60Hz <sup>1)</sup> | 40000 h                         | 32000 h                         | Direction of rotation      | bidirectional                                      |
| Lubricants                                                                             | Unirex N3                       |                                 | Frame material             | aluminum                                           |
| Regreasing device                                                                      | No                              |                                 | Coating (paint finish)     | Standard paint finish C2                           |
| Grease nipple                                                                          | -/-                             |                                 | Color, paint shade         | RAL7030                                            |
| Type of bearing                                                                        | Locating bearing DE             |                                 | Motor protection           | (B) 3 PTC thermistors - for tripping (2 terminals) |
| Condensate drainage holes                                                              | -/-                             |                                 | Method of cooling          | IC411 - self ventilated, surface cooled            |

|                          |           |                                |                     |
|--------------------------|-----------|--------------------------------|---------------------|
| Terminal box position    | top       | Max. cross-sectional area      | 4.0 mm²             |
| Material of terminal box | Aluminium | Cable diameter from ... to ... | 11.0 mm - 21.0 mm   |
| Type of terminal box     | TB1 F00   | Cable entry                    | 2xM32x1,5-1xM16x1,5 |
| Contact screw thread     | M4        | Cable gland                    | 3 plugs             |

Notes:

$I_A/I_N$  = locked rotor current / current nominal  
 $M_A/M_N$  = locked rotor torque / torque nominal  
 $M_K/M_N$  = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010  
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

|                                                                                    |                      |                 |             |                                                                                                              |                  |          |      |
|------------------------------------------------------------------------------------|----------------------|-----------------|-------------|--------------------------------------------------------------------------------------------------------------|------------------|----------|------|
| responsible dep.                                                                   | technical reference  | created by      | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                  |          |      |
| DI MC LVM                                                                          |                      | DT Configurator |             |                                                                                                              |                  |          |      |
|  | document type        |                 |             | document status                                                                                              |                  | customer |      |
|                                                                                    | datasheet            |                 |             | released                                                                                                     |                  |          |      |
|                                                                                    | title                |                 |             | document number                                                                                              |                  |          |      |
|                                                                                    | 1LE1003-1BB23-4FB4-Z |                 |             |                                                                                                              |                  |          |      |
|                                                                                    | L20                  |                 |             | rev.                                                                                                         | creation date    | language | Page |
| © Siemens AG 2021                                                                  |                      |                 |             | 01                                                                                                           | 2021-04-21 23:18 | en       | 1/2  |



**SIMOTICS GP - 112 M - IM B5 - 4p**

## Special design

|     |                      |
|-----|----------------------|
| L20 | Locating bearing, DE |
|-----|----------------------|

## Notes:

|                                                                                    |                               |                               |             |                             |                                                                                                              |                |             |  |
|------------------------------------------------------------------------------------|-------------------------------|-------------------------------|-------------|-----------------------------|--------------------------------------------------------------------------------------------------------------|----------------|-------------|--|
| responsible dep.<br>DI MC LVM                                                      | technical reference           | created by<br>DT Configurator | approved by |                             | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                |             |  |
|  | document type<br>datasheet    |                               |             | document status<br>released |                                                                                                              | customer       |             |  |
|                                                                                    | title<br>1LE1003-1BB23-4FB4-Z |                               |             | document number             |                                                                                                              |                |             |  |
| © Siemens AG 2021                                                                  | L20                           |                               |             | rev.<br>01                  | creation date<br>2021-04-21 23:18                                                                            | language<br>en | Page<br>2/2 |  |